IMPLEMENTATION OF A PARTITIONED ALGORITHM FOR SIMULATION OF LARGE CSI PROBLEMS

by

K. F. Alvin and K. C. Park

Implementation of a Partitioned Algorithm for Simulation of Large CSI Problems

K. F. Alvin and K. C. Park

Department of Aerospace Engineering Science and
Center for Space Structures and Controls
University of Colorado
Boulder, CO   80309-0429

March 1991

Report No. CU-CSSC-91-04

Summary

This report summarizes research work on the implementation of a partitioned numerical algorithm for determining the dynamic response of coupled structure/controller/estimator finite-dimensional systems. The partitioned approach leads to a set of coupled first and second-order linear differential equations which are numerically integrated with extrapolation and implicit step methods. The present software implementation, ACSIS, utilizes parallel processing techniques at various levels to optimize performance on a shared-memory concurrent/vector processing system. The current work also generalizes the form of state estimation, whereby the Kalman filtering method is recast in a second-order differential equation equivalent to and possessing the same computational advantages of the structural equations. As part of the present implementation effort, a general procedure for the design of controller and filter gains is also implemented, which utilizes the vibration characteristics of the structure to be solved. Example problems are presented which demonstrate the versatility of the code and computational efficiency of the parallel methods is examined through runtime results for these problems. A user's guide to the ACSIS program, including descriptions of input formats for the structural finite element model data and control system definition, can be found in Appendix A. The procedures and algorithm scripts related to gain design using PRO-Matlab are included in Appendix B. In Appendix C, a stability analysis for the partitioned algorithm is presented which extends previous analysis to include observer dynamics, leading to a clearly definable stability limit. The source code for the parallel implementation of ACSIS is listed in Appendix D.

1.0 Introduction

The present work on the implementation of a partitioned transient analysis algorithm for the simulation of linear Control-Structure Interaction (CSI) problems has concentrated on four major areas. The initial software implementation emphasized the user-friendly aspect and a structural dynamics-oriented interface for experienced practitioners of finite element analysis programs. Another reason for a new implementation of the algorithm was that the initial architecture of the CS3 software testbed developed by Belvin and Park [1-2] had little provision for effective parallelization. CS3 also included extensive links to optimization and optimal control algorithms which were not central to the current work and proved to be a further hinderance. This new software implementation was designated ACSIS, for Accelerated Control-Structure Interaction Simulation, and led to significant improvements in speed for particular problems on conventional serial processors due to simpler and more economical storage of primary variables. ACSIS is also versatile in its usage of a general Timoshenko beam element with pin release capability and shear correction factor adjustment, and control system definition via a single data file. A preliminary Users Guide was developed for ACSIS, and the input formats were made compatible with pre/postprocessing software developed for Sun and Silicon Graphics computers so that

1

future versions using parallel techniques via element mesh domain decompositions can rely on the same X-Window-based I/O utilities. Table 1 documents runtime comparisions of ACSIS and CS3 on a sample 48 DOF problem simulated on a Sun 3/260 workstation using a floating point accelerator.

2.0 State Estimation via Second-Order Kalman Filtering

One restriction of the CS3 software testbed was the form of dynamic observer equations used in the partitioned algorithm as developed in [2]. However, Belvin and Park [3] showed that a general Kalman filtering type of state estimation was not only possible in the partitioned solution, but could be implemented at a very small additional cost in computations by a slight modification in the way the dynamical equations of the plant are cast into first-order form for filter gain design. The methods employed in [3] have been successfully implemented into ACSIS, thereby enhancing the code's ability to handle a wide variety of state estimation schemes. This is important as the application of optimal control techniques to the state estimator problem leads to this more general form, and as the restrictions of the observer used in CS3 typically meant either discarding part of the observer gain parameters, resulting in a loss in system performance.

ACSIS retains the option of using the more resricted observer form, as well as simple full state feedback (no dynamic compensation). It is clear from examining the respective equations, that for structures with stiffness-proportional damping, the only additional calculations required for the Kalman filter is the multiplication of the L_1 gain matrix by the predicted state estimation error vector γ (see equations 25 of [3]). This is not a significant portion of the computations required at each integration step, as the dimension of γ is small (number of sensors). By far the major costs are for computing an internal force of the form $\mathbf{Kq}$, and backsolving the factored integration matrix for the estimated displacement states. This is verified numerically in the ACSIS results of Table 1 (using a restricted form of observer) and version (A1) of Table 2. The model used in Table 1 is roughly comparable to the 54 dof truss in Table 2, and both show the additional simulation time due to state estimation is roughly the same as an additional transient analysis. Finally, the Kalman filtering equations do not lead to any additional complications in parallel implementation of the overall algorithm as compared to the more restricted second-order observer developed for CS3.

3.0 Parallel Implementation of ACSIS

A primary emphasis in our work dealt with the optimization of the software implementation on a concurrent processing system. The platform chosen (primarily due to availability, initially at CU and later at NASA LaRC) was the Alliant FX/8 shared memory multiprocessor system with 8 parallel processing units and vectorization capabilities. Versions of the software have been ported to the Alliant and compiled using the Concentrix FX/Fortran optimizing compiler, which has available options for automatic vectorization and concurrency of standard, problem-independent parallel computations.

The partitioned CSI algorithm has three primary levels of parallelism in its numerics which can be exploited. At the highest level is the integration of the second-order dynamical plant (structure) and filter (estimator) equations, which as designed are of roughly equivalent size. Through the algorithm, these systems are effectively decoupled and independent at each discrete time step, and thus may be handled in parallel by invoking a compiler directive in the main program, which calls the respective subroutines simultaneously and handles re-synchronization of the execution upon their return.

At a lower level of the algorithm, the structure and state estimator equations exhibit symmetric, second-order forms typical of linear structural dynamics problems. It is well known that computations related to the formation of the internal force vector, Kq, can be re-implemented at an element level [4], which, through decomposition of the element mesh [5], can be handled in parallel within exclusive subdomains. This technique becomes particularly attractive for larger problems on more massively parallel systems; in the present work, the element-by-element (EBE) technique was not as effective as other types of parallelism. It should be noted here that the partitioned algorithm employs implicit integration methods, leading to systems of algebraic equations which are factored and solved using direct, rather than iterative, numerical methods. Therefore, formulation of the internal force vector is needed only in the formation of the known (right hand side) vector for integration of the plant and filter equations. The alternative to EBE computations is multiplication of the relevant displacement vector with the global stiffness matrix stored in profile (skyline) form. To "simulate" the advantages of local memory typical in large-scale parallel processing systems, the computed element stiffnesses were saved in shared memory for the EBE calculations, thus avoiding the need to recompute this data at each integration step. In addition, a low-overhead automatic element domain decomposition was provided for the parallel EBE method.

The final and lowest level of parallelism is obviously that of the basic matrix computations such as addition, multiplication, etc. These numerical operations are inherent in nearly all areas of the software implementation, including problem preprocessing. With the very capable optimizing compiler available on the Alliant system, this parallelism was exploited through vectorization and concurrency of the nominal source code using the FX/Fortran compiler run-time options -O -DAS -alt. The performance of the resultant executable code was examined using the Alliant's profiling capabilities, and changes to the nominal

3

source code, remaining compliant to F77, to maximize the identifiable concurrency and thus enhance the resultant speed. This was particularly useful in the profile matrix/vector multiply operation, whose speed is critical to the overall program performance.

4.0 Problem Descriptions

Three structural dynamics problems were developed for code testing at various levels of complexity. All three problems have the following common features: simulations consisted of 1000 integration steps and employed a stiffness-proportional damping. The damping was not needed for algorithm stability, but to ensure consistency between the examples and because the existence of damping in the plant equations has a strong influence on program speed. The Kalman filter models were of second-order form [2] and equivalent in size to their respective plant models. For controlled simulations, the control system began operating after 100 integration steps, and all gain matrices were full (i.e. all model states influence all actuators and are influenced by all sensors). Additional specific information for the problems follow.

A. Axial Vibration of Elastic Bar (Spring Model)

# Nodes:	3 free, 1 fixed
# Elements:	3
# Degrees of freedom:	3
# Actuators:	1
# Sensors:	1
Disturbance:	Initial displacement

B. Planar Vibration of Space Truss (Truss Model)

# Nodes:	18 free
# Elements:	33
# Degrees of freedom:	54
# Actuators:	4
# Sensors:	6
Disturbance:	Bang-bang type sinusoidal applied force

C. General 3D Vibration of EPS Satellite Reboost (EPS7 Model)

# Nodes:	97 free
# Elements:	256
# Degrees of freedom:	582
# Actuators:	18
# Sensors:	18
Disturbance:	Bang-bang type square wave applied force

As can be seen, the problem sizes are roughly three different orders of magnitude, with corresponding increases in the sizes of the control systems. Appendix B includes routines using Matlab for the design of control and filter gains which were used for the control system design of all three example problems. An illustration of the EPS model is shown in Figure 1.

5.0 Performance Assessment

Table 2 compares CPU runtimes on the Alliant computer (using the UNIX "time" command) for distinct versions of the software. Version (A1) is the nominal F77 program code compiled without any performance-enhancing options, while version (A2) invokes automatic vectorization and concurrency of low-level, problem-independent computations such as vector addition and inner products. The performance improvements are significant, especially for the large EPS7 model, where the speed-up factor is 35-37.

Version (A3) also uses the compiler options from (A2), but in addition has a compiler directive added to the main program which allows the plant and filter integration subroutines to be called in parallel. This does not affect the transient response results as that analysis option bypasses the altered code, but for controlled response there is some effect on performance. If filtering is used, which results in a significant increase in computation, the directive can lead to some increased speed as can be seen for the spring and truss problems. There can also, however, be a reduction in performance as compared to (A2) if the finite amount of processors and vector units are used in a less efficient way. This appears to be the case for the large EPS problem, where the "overhead" introduced by the directive, and its effect on processor assignment, is greater than the improvement generated by the manually-invoked parallel construct.

Table 3 shows CPU run times for ACSIS using E-B-E computations, which, as mentioned previously did not lead to better performance on the example problems using the Alliant system. This appears to be due to the lack of effective vectorization of the individual element computations when forming the internal force via the EBE method. To determine whether the EBE method effectively lead slower speeds through increased numbers of computations, version (A2) (see above) was altered by removing compiler optimization of the profile matrix/vector multiply routine (the alternate method to EBE). The resultant runtimes matched almost exactly with those of version (A4), leading to the conclusion that both methods require roughly the same amount of computations, but differ in how they can be optimized on the Alliant system. The matrix/vector multiply operation, in this environment, can exploit both vectorization and concurrency through the complier's performance options; this can be examined in the compiler output. The EBE computations, at the element level, do not vectorize because the parts of the global displacement and force vectors being operated on per element are not contiguous. In version (A5), the elements within each subdomain of the mesh are computed in parallel, leading to some performance

Overall, versions (A2) and (A3) provide the best code performance for the hardware available. Parallelizing the observer and structure (A3) leads to mixed results; improvement for the small spring and truss problems, but not for the large EPS model. Element-by-element computations do not improve code performance over compiler optimization via vectorization and concurrency for this platform. Reimplementation of the algorithm lead to a 5:1 improvement over the CS3 testbed software on a serial computer (Table 1). Further optimization of ACSIS on the Alliant FX/8 lead to an additional 30:1 improvement in runtimes for large-order systems such as the 582 dof EPS model. Time history responses of selected variables for the example problems are shown in Figures 2 through 10. For Figures 8 through 10, the u_x, u_y, u_z displacements plotted are located at node 45, which is located at the vertex of the large antenna of the EPS model (see Figure 1).

6.0 Conclusions

The present work has demonstrated the efficiency of a streamlined simulation code for the analysis of large-order CSI systems and the viability of the continuous second-order Kalman filtering equations for state estimation. These methods show the versatility of the partitioned CSI integration algorithm and the promise of its application to real-time simulation. It is evident, however, that the use of element-by-element computational techniques requires the development of innovative algorithms for effective implementation on massively parallel processing systems. Future work in this area will include integrating algorithms for on-line system identification and applying these capabilities to the problem of real-time control.

Simulation	CS3	ACSIS
Transient	439.2	98.8
Full State Feedback	688.2	181.5
FSFB with Observer	1156.7	282.3

Table 1: Comparison of Runtime Speeds for CS3 and ACSIS
on a Sun 3/260 System

Model	Problem Type	(A1) Nominal Code	(A2) Compiler Optimized	(A3) Parallel Observer
3 DOF Spring	Transient	6.6	2.1	2.1
	FSFB	8.0	3.3	3.3
	K. Filter	12.3	3.5	3.3
54 DOF Truss	Transient	78.2	5.7	5.6
	FSFB	97.1	9.4	10.2
	K.Filter	170.7	13.0	10.7
582 DOF EPS7	Transient	3506.	98.6	100.3
	FSFB	7040.	190.2	294.5
	K. Filter	n/a	284.2	312.5

Table 2: CPU Results for Versions of ACSIS

7

Model	Problem Type	(A4) E-B-E Computation	(A5) Parallel E-B-E	(A6) Parallel Obs. & EBE
3 DOF Spring	Transient	3.8	3.3	3.3
	FSFB	4.9	4.4	4.9
	K. Filter	6.6	5.6	5.0
54 DOF Truss	Transient	31.7	13.0	13.0
	FSFB	35.5	16.9	35.6
	K.Filter	62.6	27.3	36.2
582 DOF EPS7	Transient	391.7	153.9	n/a
	FSFB	485.9	245.9	n/a
	K. Filter	n/a	n/a	n/a

Table 3: CPU Results for ACSIS with EBE Computations

Figure 1: EPS Finite Element Model

Spring Model: Open Loop Transient Response

Figure 2: Spring Transient Response

Spring Model: Full State Feedback Response

Figure 3: Spring FSFB Response

Spring Model: Controlled Response w/Kalman Filter

——— Node 3, ux

Figure 4: Spring Response w/Filter

Truss Model: Open Loop Transient Response

Figure 5: Truss Transient Response

Truss Model: Full State Feedback Response

Figure 6: Truss FSFB Response

Truss Model: Controlled Response w/Kalman Filter

Figure 7: Truss Response w/Filter

EPS7 Model: Open Loop Transient Response

Figure 8: EPS Transient Response

16

EPS7 Model: Full State Feedback Response

Figure 9: EPS FSFB Response

EPS7 Model: Controlled Response w/Kalman Filter

Figure 10: EPS Response w/Filter

18

REFERENCES

1. Belvin, W. K., "Simulation and Interdisciplinary Design Methdology for Control-Structure Interaction Systems," PhD Thesis, Center for Space Structures and Controls, University of Colorado, Report No. CU-CSSC-89-10, July, 1989.

2. Park, K. C. and Belvin, W. K., "Partitioned Procedures for Control-Structure Interaction Simulations," *Journal of Guidance, Control, and Dynamics,* Vol. 14, No. 1, Jan.-Feb. 1991, pp. 59-67.

3. Park, K. C. and Belvin, W. K. and K. F. Alvin, "Discrete Second-Order Kalman Filtering Equations for Control-Structure Interaction Simulations," *Report No. CU-CSSC-89-08*, Center for Space Structures and Controls, University of Colorado, April 1989 (Submitted for publication in J. Guidance, Control and Dynamics).

4. Farhat, C. and Crivelli, L., "A General Approach to Nonlinear FE Computations on Shared Memory Multiprocessors," *Comp. Methods in Applied Mech. Eng.,* Vol. 72, No. 2, pp. 126-152 (1989)

5. Farhat, C., "On the Mapping of Massively Parallel Processors onto Finite Element Graphs," *Report No. CU-CSSC-88-02*, Center for Space Structures and Controls, University of Colorado, April 1988

APPENDIX A

ACSIS User's Manual

Accelerated
Control
Structure
Interaction
Simulation

Introduction

ACSIS is an analysis program for full-order simulation of control-structure interaction
(CSI) problems. The CSI simulation is carried out using a partitioned analysis pro-
cedure which treats the structure (or plant), the observer, and the controller/observer
interaction terms as separate entities. This procedure allows ACSIS to maintain rela-
tively small, sparse matrix equations when compared to the process of assembling the
computational elements into a single set of equations of motion and solving simultane-
ously. Although this software can also carry out modal analysis, the transient response
and CSI simulation are done in real space using the entire finite element model. (For
more information, see Ref. 2 of report, p. 14)

The ACSIS program is run using two previously prepared data input files and interactive
input of run options. The two data input files are the finite element input file and the
controller definition file.

Interactive Options

The run options are as follows, note that no defaults exist, data must be input each time it is requested for each item requested except during a background run. Files may be given any names, example names are given only to match the truss example at the back of this manual.

Please input analysis type:

This option is for selecting modal analysis, CSI simulation or the transient response of a structure. Not all interactive inputs are required for each analysis type.

Do you wish to save an input file? (y or n)

This option creates a file which saves all the interactive input options. ACSIS can be background run with minor option changes by editing this file and then directing the screen input to this file. This file is very different for each analysis type . (To do this run with the example names after running acsis.exe once interactively, the command would be: acsis.exe <INP_truss> &.

Name of save input file? (filename)

This question asks for the name under which to save the interactive input. example name: INP_truss

Finite Element Model Input File Name (filename):

This file should contain all the finite element nodes, mesh, materials, properties, lumped inertias, fixations, and initial velocity and displacement conditions. It must be prepared in advance in the card format specified later. example name: FEM_truss

Number of modes desired? ·

This only appears in the modal analysis to request the number of modes to be output. The actual analysis is carried out with double this number of modes for accuracy.

Controller Definition File Name:

This only appears for the CSI simulation. The file should contain the actuator and sensor locations, control gains, and observer gains. It also must be prepared in advance in card format. example name: CON_truss

Please input type of control::

This option is for selecting the form of control law equations used in the CSI simulation. Full state feedback uses the current states of the plant (structure) to determine the control via constant gain matrices. Second-order observer uses only the L2 filter gain matrix of a Kalman filtering type of state estimation where the state variables are position and velocity. The Kalman filter option allows the use of a full set of filter gains, but the gain design must come from a alternate variable casting using position and generalized momenta.

22

Initial time, final time, control-on time, step size:

Data format is four columns for CSI, but only three columns for transient response since the control-on time part is deleted.

Forcing function ID, scale factor, damping coeff- a,b:

In order for any time dependent forcing function to be easily implemented despite variable time step sizes, the forcing functions must be entered into the subroutine forces.f. The format is to assign each new forcing function an ID number in a elseif statement. An example of forces.f is included at the back of the manual. Then forces.f must be recompiled into an object file and acsis.exe relinked. This is easily done by typing make which detects changes to the fortran files and does only the necessary compiling. A particular forcing function is chosen by entering its ID number in the first column, in addition the force can be scaled by a constant using the scaling factor in the second column. The Rayleigh damping coefficients a and b are the third and fourth columns.

Phase lag fix? (y or n):

Specifies whether to include an extra iteration of control and sensor state prediction at each integration step to improve accuracy. Not generally needed unless the user is investigating the source of instability in a simulation and needs to test the sensitivity of the response to the partitioned algorithm's extrapolation method.

Gain scale factors (4 total):

These scaling factors are, in order: the F1 control gain matrix (displacement), F2 control gain matrix (velocity), L1 and L2 state estimator filter gain matrix. This question appears only for CSI.

ACSIS has two types of output options. The first is the displacement or velocity motion of up to twenty separate degrees of freedom. Interactive questions are, 'Number of displacement results to output (max 10)' followed by as many 'Input node #, dof for displacement output #' as necessary. Then these repeat for velocity results. The name of the file where the output will be stored is requested by 'Output file name? (filename).' example name: OUT_truss. The second output option saves the displacement of all nodes at any time step where output is sent (see next entry). The format is suitable for animation of the entire structure. Question asks 'Animation Output? (y or n)' then for an animation filename if necessary.

Send output every how many steps?

This option affects both output options to reduce the size of the output and animation files. It causes output to only be sent after a integer number of time step iterations. To get output each time step, simply enter 1.

Finite Element Input File

The finite element input file consists of title cards followed by columns of data. The title cards can be in any order, but they must be all capitalized with the appropriate number of columns of data for each card. The program reads rows of data until encountering a new card. Data which represents an integer value may be entered with a decimal point while real data may be entered without a decimal point as necessary. Any line beginning with a * anywhere in the file is ignored and can be used to insert comments. Any blank line will result in a read error.

NODES

Each node must be defined on a separate line. Columns can be separated by any number of spaces or a comma. Data format is four columns: node number, x-coordinate, y-coordinate, z-coordinate.

TOPOLOGY

Each element must be defined on a separate line. Truss elements require two nodes then two columns of zeroes. (Truss elements would also require pin releases in ATTRIBUTES below.) Beam elements require two nodes then a third reference node representing a point in the xz plane of the beam and then a column of zeroes. Element type refers to finite elment formalation. (Currently only type 1 = timeshenko beam element is now available.) Data format is six columns: element number, element type, node #1, node #2, node #3, node #4.

ATTRIBUTES

Each element is characterized by an ID number from each of the MATERIAL and PROP-ERTIES cards below. Each element also has six pin release codes. The first code is for longitudinal stiffness, the second code is for torsional stiffness, the third and fifth codes are bending stiffness at each end in the y direction and must be the same value, and the fourth and sixth codes are for bending stiffness in the z direction and also must be the same. (0 is stiff, 1 is released.) Data format is nine columns: element number, material type, property type, and six pin release codes.

MATERIAL

The material data is formatted in four columns: material type, Young's modulus, shear modulus and density of the material.

PROPERTIES

The properties data is formatted in six columns: property type, cross sectional area of the element,$I_y * I_x$, I_y, I_z, shear shape factor SSF2, shear shape factor SSF3.

FIXITY

Nodes with any fixations are defined here in the finite element file. The nodes must be entered with the fixity of all six of their DOF's, restrained or not. (1 is restrained, 0 is free) Data format is seven columns: node number, x, y, z, ϕ_x, ϕ_y, ϕ_z.

INERTIA

All lumped inertias must be entered with each separate DOF on an individual line. Therefore a single node could take up to six lines to define. Data format is three columns: node number, DOF number (1-6), and value of inertia.

INITIAL CONDITIONS

All initial displacement and velocity conditions are entered into the finite element file. Data format is four columns: node number, DOF number (1-6), initial displacement, and initial velocity.

END

End of file.

Controller Definition Cards

The controller defintion file also consists of title cards followed by data entry. Each card must be followed by the appropriate number of columns of data and in some cases the appropriate number of rows. Integers can be entered in real format and vice versa if necessary. Any blank line will result in a read error.

NACT

Number of actuators in the entire control system.

BMAT

This entry creates the actuator position matrix or B matrix. There should be one row for each actuator, data format is four columns: node number, DOF number (1-6), actuator number, and sensitivity.

NSEN

Number of sensors in the entire controls system.

HDMA

This entry creates the matrix of displacement sensor locations. One row per displacement sensor, data format is four columns: node number, DOF number (1-6), sensor number, and sensitivity.

HVMA

This entry creates the matrix of velocity sensor locations. One row per velocity sensor, data format is four columns: node number, DOF number (1-6), sensor number, and sensitivity.

F1GA

This is a list of the F1 or displacement control gains. The data format is four columns: node number, DOF number (1-6), actuator number, and value of gain.

F2GA

This is a list of the F2 or velocity control gains. The data format is four columns: node number, DOF number (1-6), actuator number, and value of gain.

L1GA

This is a list of the state estimator L1 filter gains. The data format is four columns: node number, DOF number (1-6), actuator number, and value of gain.

L2GA

This is a list of the state estimator L2 filter gains. The data format is four columns: node number, DOF number (1-6), actuator number, and value of gain.

END

End of file.

Examples

This section includes all the files and procedures needed to run all three analysis on a simple elastic bar problem. The naming of the files is a simple and easy to remember system, however no particular format is necessary.

The finite element file was created simply by typing the node locations, connectivity (topology), etc. with a text editor.

File: FEM_spring

```
*
MESH
*
NODES
  1    0.00 0.00 0.00
  2    1.00 0.00 0.00
  3    2.00 0.00 0.00
  4    3.00 0.00 0.00
TOPOLOGY
  1    1   1   2   0   0
  2    1   2   3   0   0
  3    1   3   4   0   0
ATTRIBUTES
  1    1   1   0 1 1 1 1 1
  2    1   1   0 1 1 1 1 1
  3    1   1   0 1 1 1 1 1
MATERIAL
  1  1000.   0.0   0.0
PROPERTIES
```

```
 1  1.00   0.00   0.00   0.00 0.0 0.0
FIXITY
 1  1 1 1 1 1 1
 2  0 1 1 1 1 1
 3  0 1 1 1 1 1
 4  0 1 1 1 1 1
INERTIA
 2  1  0.100
 3  1  0.100
 4  1  0.100
INITIAL
 3  1  0.100 0.000
END
```

The modal analysis only requires the number of modes desired in addition to the finite element file. The file INP_spring0 documents the interactive inputs used in the modal analysis. The results are saved in file EIG_spring.

File: INP_spring0

```
-1
n
        *  ACSIS input file,two lines above are
        *  analysis type and save input file. Do
        *  not change them by editing this file.
        *  Finite element input file?(filename)
FEM_spring
        *  Number of modes desired?
   3
        *  Output file?(filename)
EIG_spring
```

File: EIG_spring

```
                  SUBSPACE ITERATION ROUTINE

 NB OF EIGENVALUES=     3
 NB OF VECTOR=     3
 NB OF DOF=    3
 TOLERANCE= 1.000E-04

 NB OF RIGID MODES=     0


        ITERATION NO     1
```

```
   1.000E+00   1.000E+00   1.000E+00
      ITERATION NO    2
   1.297E-14   3.194E-14   3.899E-14
EIGEN ANALYSIS RESULTS:
                      RADIAL      CYCLIC
 MODE     EIGENVALUE  FREQUENCY   FREQUENCY
 ----     ----------  ---------   ---------

   1       1980.6      44.504      7.0831
   2       15550.      124.70      19.846
   3       32470.      180.19      28.679
EIGENVECTORS:

   1   2.3305      1.8689      -1.0372      0.        0.
   2   1.8689     -1.0372       2.3305      0.        0.
   3   1.0372     -2.3305      -1.8689      0.        0.
MASS MATRIX DIAGONAL:
   2  1  3      1.0000000000000D-01
   3  1  2      1.0000000000000D-01
   4  1  1      1.0000000000000D-01
```

To run the transient response of the structure, a forcing function or initial condition would be needed to excite the structure. An initial condition would be added to the finite element file. A forcing function must be added to forces.f with a new ID number, then this number given as interactive input. In this case, an initial displacement acts on the second degree of freedom, which is defined in the finite element model input file. The file INP_spring1 documents the interactive inputs used in the transient analysis.

File: INP_spring1

```
-3
n
        *  ACSIS input file,two lines above are
        *  analysis type and save input file. Do
        *  not change them by editing this file.
        *  Finite element input file?(filename)
FEM_spring
                  *  Initial, final, step size?
   0.00000000   1.00000000     0.00100000
        *  Forcing function,scale f, damping a,b?
   0       0.000000   0.00000000   0.00002000
        *  Output file name?(filename)
OUT_spring
        *  Number of displacement outputs?
   1
        3          1
        *  Number of velocity outputs?
```

28

```
        0
            *   Send output every how many steps?
        1
            *   Send animation output?(y or n)
n
```

In addition to the finite element file, the interactive input, and an excitation, CSI simulation requires a controller definition file. A full state feedback controller for the truss structure is defined in CON_spring.

File: CON_spring

```
NACT
 1
BMAT
 3  1  1  1.0
F1GAIN
   2  1  1       193.31415000000
   3  1  1      1574.6315000000
   4  1  1     -1669.0460000000
F2GAIN
   2  1  1        20.774256000000
   3  1  1        27.790403000000
   4  1  1        10.780212000000
NSEN
 1
HVMAT
 3  1  1  1.0
L1GAIN
   2  1  1.       8.7928909000000D-02
   3  1  1.      -4.8807901000000D-02
   4  1  1        3.0102735000000D-03
L2GAIN
   2  1  1        1.0380932000000D-01
   3  1  1        6.1410130000000
   4  1  1       -3.0608725000000
END
```

Then if acsis.exe is run interactively and the input is saved, the file INP_spring2 can be produced. The file could be edited to change the input files, the output file, the forcing function ID, the length of simulation, control-on time, etc. Then to run it again, type acsis.exe<INP_spring2> scr &. The scr is a scratch file which will store the screen output.

File: INP_spring2

```
-2
```

n
```
        *   ACSIS input file,two lines above are
        *   analysis type and save input file. Do
        *   not change them by editing this file.
        *   Finite element input file?(filename)
FEM_spring
        *   Controller file name?(filename)
CON_spring
        *   Please input type of control:
         3
        *   Initial,final,control-on,step size?
    0.00000000     1.00000000     0.10000000     0.00100000
        *   Forcing function,scale f, damping a,b?
     0         0.000000   0.00000000   0.00002000
        *  Phase lag fix?(y or n)
n
        *   Gain scale factors (4 total)?
    1.00000000     1.00000000     1.00000000     1.00000000
        *   Output file name?(filename)
OUT_spring
        *   Number of displacement outputs?
    1
        3          1
        *   Number of velocity outputs?
    0
        *   Send output every how many steps?
    1
        *   Send animation output?(y or n)
n
```

APPENDIX B

Matlab Procedure and Scripts for Controller and Kalman Filter Gain Designs

Introduction

In order to retain simplicity in the ACSIS code for parallel implementation purposes, no control system design algorithms were included. Instead, using modal data output from the eigenmode analysis module of ACSIS, a procedure was developed using the Pro-Matlab and its Control System Toolbox, which includes algorithm scripts for optimal control solutions via the solution of an algebraic Ricatti equation. In order to accomodate large order dynamical systems, the design is accomplished in the uncoupled normal modes domain, using the available lowest eigenmodes from ACSIS.

The procedure begins by copying and editing the mode data output from ACSIS (see the listing for EIG_spring in Appendix A) into readable variables for input to Matlab. The typical approach was to create one file as a Matlab script (i.e. a ".m" file), with the eigenvalues, eigenvectors, and mass/dof data from ACSIS at the beginning, followed by actuator and sensor influence matrices (related to the physical degrees of freedom), the objective function weighting matrices, and the function which calls other Matlab scripts to determine the solution. An example of the above input for the spring problem described in Appendix A is in file EIG_spring.m, which is listed below. Compare this the the ACSIS mode data output shown in Appendix A to see how the editing was accomplished, and the additional control design data added

File: EIG_spring.m

```
lam = [   1980.6
          15550.
          32470.    ];
v1=[1   2.3305      1.8689      -1.0372       0.        0.
      2   1.8689      -1.0372      2.3305       0.        0.
      3   1.0372      -2.3305      -1.8689       0.        0.    ];
m=[  2   1   3     1.00000000000000D-01
    3   1   2     1.00000000000000D-01
    4   1   1     1.00000000000000D-01];
t=[v1(:,2:4)];
qb=zeros(3,1);
qb(2,1)=1.0;
hd=zeros(1,3);
hv=zeros(1,3);
hv(1,2)=1.0;
qv=[1;.5;.1];
q=diag([qv;qv]);
r=.0001*eye(1);
[f1,f2]=mlqr(lam,t,m,qb,q,r,3);
qv=[1;1;1];
q=diag([qv;qv]);
r=100*eye(1);
[k1,k2]=mkf(lam,t,m,hd,hv,q,r,3);
save f1out f1 /ascii
save f2out f2 /ascii
```

```
save klout kl /ascii
save k2out k2 /ascii
```

The scripts mlqr.m and mkf.m were written to accept as input the vector of eigenvalues, the eigenvector matrix (orthogonal vectors stored in columns), a matrix of node, component, d.o.f, mass data, and the actuator (or sensor) influence matrix and weighting matrices. The scripts output the gain results in four-column arrays, with one gain per row, and the corresonding node number, displacement component, and actuator (or sensor) identification. The top-level problem script (listed above) then saves the output in external files and the analysis is complete. The design scripts (listed below) also include checks on controllability and observability of the system based on the modal data and influence matrices defined, and produce plots of the closed loop poles resulting from the gain design. This aids the analyst in assessing the expected performance (and stability) of the exact system before moving the data back to ACSIS for simulation. The script contrank.m finds the rank of the controllability matrix through iterative rank calculations of submatrices so as to avoid the illconditioning experienced in the full matrix. This is both faster and more accurate for determining whether a particular actuator placement has full control of the included structural modes.

File: mlqr.m

```
function[F1out,F2out]=mlqr(lam,t,m,qb,Q,R,nmode)
%
%  Controller gain design for second-order
%    structural system via given eigenmodes.
%    Gains are transformed to be coefficents
%    of structural variables (disp,velocity);
%    i.e. plant is second-order, of size ndof.
%
%  Arguments:
%
%    lam:  vector of eigenvalues (nmode x 1)
%    t:  matrix of eigenvctors (ndof x nmode)
%    m:  mass diagonal and dof mapping info (ndof x 4)
%    qb:  actuator position influence matrix (nact x ndof)
%    Q: optimal design state weighting matrix (2*nmode x 2*nmode)
%    R: optimal design feedbk weight. matrix (nact x nact)
%
%    F1out:  F1 gain matrix for 2nd-order plant
%    F2out:  F2 gain matrix for 2nd-order plant
%
%  Written by K.F. Alvin
%
format short e
nmodmax=length(lam);
[ndof,nact]=size(qb);
%
%  Variables:
%    mass:  mass matrix
```

33

```
%    A: state transition matrix
%    B: actuator influence matrix
%    G: control gain matrix
%
massd(m(:,3))=m(:,4);
mass=diag(massd);
A=[zeros(nmode),eye(nmode);-1*diag(lam(1:nmode)),zeros(nmode)];
Amax=[zeros(nmodmax),eye(nmodmax);-1*diag(lam),zeros(nmodmax)];
B=[zeros(nmode,nact);t(:,1:nmode)'*qb];
Bmax=[zeros(nmodmax,nact);t'*qb];
disp('Number of structural modes and actuators used:')
disp([nmode,nact])
disp('Rank of the controllability matrix:')
disp(contrank(A,B))
disp('Determining controller gains for given system...')
G=lqr(A,B,Q,R);
wmax=1.1*max(sqrt(lam));
axis([-wmax,wmax,-wmax,wmax]);
plot(eig(A-B*G),'*')
grid
title('Roots of controlled system')
hold
pause
%
%  partition gain matrix
%
G1=G(:,1:nmode);
G2=G(:,nmode+1:nmode+nmode);
%
%  Transform resultant gain matrices for use in
%    partitioned csi algorithm using second-order
%    structure(plant) equations.
%
disp('Mapping gains back to physical domain...')
f1=G1*t(:,1:nmode)'*mass;
f2=G2*t(:,1:nmode)'*mass;
%
%  find modal damping ratios of controller for calulated gains:
%
Gmax=[f1*t,f2*t];
lambda=eig(Amax-Bmax*Gmax);
plot(lambda,'*')
pause
nfreq=sqrt(imag(lambda).^2 + real(lambda).^2);
mdamp=-real(lambda)./nfreq;
disp('Resultant modal damping ratios for controller:')
disp(['  Damping ','   Damped Freq (rad/s)  '])
disp([mdamp,nfreq.*sqrt(1-mdamp.^2),lambda])
bdamp=max(-2*mdamp./nfreq);
disp('Estimated minimum stiffness damping coefficient necessary')
disp(' to stabilize residual modes due to gain roundoff accumulation:')
disp(bdamp)
disp('Writing gains in node correspondence output form...')
```

```
F1out=zeros(nact*ndof,4);
F2out=zeros(nact*ndof,4);
for i=1:nact;
  kmin=(i-1)*ndof+1;
  kmax=i*ndof;
  F1out(kmin:kmax,:)=[m(:,1:2),i*ones(ndof,1),f1(i,m(:,3))'];
  F2out(kmin:kmax,:)=[m(:,1:2),i*ones(ndof,1),f2(i,m(:,3))'];
end;
disp('Finished mlqr')
```

File: mkf.m

```
function[L1out,L2out]=mkf(lam,t,m,hd,hv,Q,R,nmode)
%
%   Kalman filter design for second-order
%     structural system via given eigenmodes
%     and transformed to independent
%     displacement/gen. momentum variable
%     casting for partitioned csi transient
%     analysis.  See Belvin/Park paper for
%     filter variable definitions.
%
%   Arguments:
%
%     lam:  vector of eigenvalues (nmode x 1)
%     t:  matrix of eigenvctors (ndof x nmode)
%     m:  mass diagonal and dof mapping info (ndof x 4)
%     hd:  sensor position influence matrix (nsen x ndof)
%     hv:  velocity position influence matrix (nsen x ndof)
%     Q: optimal design state weighting matrix (2*nmode x 2*nmode)
%     R: optimal design feedbk weight. matrix (nsen x nsen)
%
%     L1out:  L1 gain matrix for 2nd-order filter
%     L2out:      L2 gain matrix for 2nd-order filter
%
%   Written by K.F. Alvin
%
format short e
nmodmax=length(lam);
[nsen,ndof]=size(hd);
%
%   Variables:
%     mass:  mass matrix
%     A: state transition matrix
%     G: noise influence matrix
%     C: output influence matrix
%     K: filter gain matrix
%
massd(m(:,3))=m(:,4);
mass=diag(massd);
A=[zeros(nmode),eye(nmode);-1*diag(lam(1:nmode)),zeros(nmode)];
Amax=[zeros(nmodmax),eye(nmodmax);-1*diag(lam),zeros(nmodmax)];
```

35

```
G=eye(nmode+nmode);
C=[hd*t(:,1:nmode),hv*t(:,1:nmode)];
Cmax=[hd*t,hv*t];
disp('Number of structural modes and sensors used:')
disp([nmode,nsen])
disp('Rank of the observability matrix:')
disp(contrank(A',C'))
disp('Determining filter gains for given system...')
K=lqe(A,G,C,Q,R);
%
%   partition gain matrix
%
K1=K(1:nmode,:);
K2=K(nmode+1:nmode+nmode,:);
Kmax=[K1;zeros(nmodmax-nmode,nsen);K2;zeros(nmodmax-nmode,nsen)];
%
%   find modal damping ratios of filter for calulated gains:
%
lambda=eig(Amax-Kmax*Cmax);
plot(lambda,'+')
hold
pause
a1=-real(lambda);
b1=imag(lambda);
disp('Resultant modal damping ratios for filter:')
disp(['  Damping  ','  Freq (rad/s)  '])
disp([a1./sqrt(a1.^2+b1.^2),b1])
%
%   Transform resultant gain matrices for use in
%     partitioned csi algorithm using second-order
%     Kalman filter approach.
%
disp('Mapping gains back to physical domain...')
l1=t(:,1:nmode)*K1;
l2=mass*t(:,1:nmode)*K2;
disp('Writing gains in node correspondence output form...')
L1out=zeros(nsen*ndof,4);
L2out=zeros(nsen*ndof,4);
for i=1:nsen;
 kmin=(i-1)*ndof+1;
 kmax=i*ndof;
 L1out(kmin:kmax,:)=[m(:,1:2),i*ones(ndof,1),l1(m(:,3),i)];
 L2out(kmin:kmax,:)=[m(:,1:2),i*ones(ndof,1),l2(m(:,3),i)];
end;
disp('Finished mkf')
```

File: contrank.m

```
function maxrank=contrank(a,b)
maxrank=0;
[nstate,nact]=size(b);
i=0;
```

```
mat=b;
newrank=rank(mat);
while newrank > maxrank
   maxrank=newrank;
   i=i+1;
   mat=[mat,(a^i)*b];
   newrank=rank(mat);
   if newrank==nstate
     maxrank=newrank;
   end
end
```

Unfortunately, the external files created from Matlab with the gain results are written completely in terms of real numbers, whereas the first three columns are actually to be read by ACSIS as integers (they are used as indices). A separate utility was written to convert the format of these files; the source code is listed below. On Unix systems, the user simply assigns the standard input to be the current data file created by Matlab, and gives another file name for the standard output. The code is basically just a filter to change the three columns of indices to integers. The output can then be pasted directly into the control definition file used by ACSIS.

File: convcont.f

```
      program convcont

      parameter (NMAX=100000)
      real*8 f(NMAX),v(4)
      integer node(NMAX),dof(NMAX),act(NMAX)

      n=0

100   read (*,*,err=200,end=200) (v(i),i=1,4)
      n=n+1
      node(n)=int(v(1))
      dof(n) =int(v(2))
      act(n) =int(v(3))
      f(n)    =v(4)
      goto 100

200   do 300 i=1,n
         print *, node(i),dof(i),act(i),f(i)
300      continue

      end
```

APPENDIX C

Stability Analysis of a
CSI Partitioned Simulation
Algorithm with State Estimator

The equation of the open-loop plant without passive damping in modal second-order form is

$$\ddot{q} + \omega^2 q = u \tag{1}$$

The controller uses a second-order observer to estimate the plant state, along with a full-state feedback control gain design.

$$
\begin{aligned}
u &= -\left(\eta\omega^2 p + \zeta\omega\dot{p}\right) \\
\ddot{p} + \omega^2 p &= u + \xi\gamma \\
\gamma &= z - \dot{p} \\
z &= \dot{q}
\end{aligned}
\tag{2}
$$

where q and p are the plant and estimator states, respectively, u is the control force, γ is the state estimation error, z is the sensor output, and η, ζ, ξ are gain coefficients for position and velocity feedback, and the estimator filter.

·The partitioned analysis procedure uses a stabilized form of the control law and estimation error determination to reduce inaccuracies associated with the extrapolation of variables in the controller force prediction. A first-order filtering is achieved by taking the time derivative of (2a,c),

$$
\begin{aligned}
\dot{u} &= -\eta\omega^2\dot{p} - \zeta\omega\ddot{p} \\
\dot{\gamma} &= \dot{z} - \ddot{p}
\end{aligned}
\tag{3}
$$

and then embedding the equations of motion through substitution for $\ddot{p}$. This leads to the following two coupled, first-order differential equations for the prediction of the control force u and state error γ.

$$
\left\{\begin{array}{c} \dot{u} \\ \dot{\gamma} \end{array}\right\} + \begin{bmatrix} \zeta\omega & \zeta\xi\omega \\ 1 & \xi \end{bmatrix} \left\{\begin{array}{c} u \\ \gamma \end{array}\right\} = \left\{\begin{array}{c} 0 \\ \dot{z} \end{array}\right\} + \left\{\begin{array}{c} \zeta\omega^3 \\ \omega^2 \end{array}\right\} p - \left\{\begin{array}{c} \eta\omega^2 \\ 0 \end{array}\right\} \dot{p} \tag{4}
$$

Time discretization of (4) using an implicit midpoint rule leads to the following coupled difference equation:

$$
\begin{bmatrix} 1 + \delta\zeta\omega & \delta\zeta\xi\omega \\ \delta & 1 + \delta\xi \end{bmatrix} \left\{\begin{array}{c} u^{n+\frac{1}{2}} \\ \gamma^{n+\frac{1}{2}} \end{array}\right\} = \left\{\begin{array}{c} 0 \\ z_p^{n+\frac{1}{2}} \end{array}\right\} + \left\{\begin{array}{c} \delta\zeta\omega^3 - \eta\omega^2 \\ \delta\omega^2 \end{array}\right\} p_p^{n+\frac{1}{2}} - \left\{\begin{array}{c} \zeta\omega \\ 1 \end{array}\right\} \dot{p}^n \tag{5}
$$

where $\delta \equiv$ half-step size $= \frac{h}{2}$. Solving this equation requires knowledge of the plant (to obtain sensor output) and observer states. These values are extrapolated as:

$$
\begin{aligned}
p_p^{n+\frac{1}{2}} &= p^n + \delta\dot{p}^n \\
z_p^{n+\frac{1}{2}} &= \dot{q}_p^{n+\frac{1}{2}} = \dot{q}^n
\end{aligned}
\tag{6}
$$

Using these equations to obtain $u^{n+\frac{1}{2}}$ and $\gamma^{n+\frac{1}{2}}$ allows the plant and observer equations to be solved independently. Midpoint time integration of (1) and (2b) leads to the following equations:

$$\left(1+\delta^2\omega^2\right)q^{n+\frac{1}{2}} = \delta^2 u^{n+\frac{1}{2}} + q^n + \delta\dot{q}^n$$

$$\left(1+\delta^2\omega^2\right)p^{n+\frac{1}{2}} = \delta^2 u^{n+\frac{1}{2}} + p^n + \delta\dot{p}^n + \delta^2\xi\gamma^{n+\frac{1}{2}}$$

$$\dot{q}^{n+\frac{1}{2}} = \frac{1}{\delta}\left(q^{n+\frac{1}{2}} - q^n\right)$$

$$\dot{p}^{n+\frac{1}{2}} = \frac{1}{\delta}\left(p^{n+\frac{1}{2}} - p^n\right) \tag{7}$$

$$q^{n+1} = 2q^{n+\frac{1}{2}} - q^n$$

$$p^{n+1} = 2q^{n+\frac{1}{2}} - q^n$$

$$\dot{q}^{n+1} = 2\dot{q}^{n+\frac{1}{2}} - \dot{q}^n$$

$$\dot{p}^{n+1} = 2\dot{q}^{n+\frac{1}{2}} - \dot{q}^n$$

Computational stability of the modal form of the CSI partitioned equations of motion using the aforementioned time discretization can be assessed by seeking a nontrivial solution of

$$\left\{\begin{array}{c} q^{n+1} \\ p^{n+1} \\ \dot{q}^{n+1} \\ \dot{p}^{n+1} \end{array}\right\} = \lambda \left\{\begin{array}{c} q^n \\ p^n \\ \dot{q}^n \\ \dot{p}^n \end{array}\right\} \tag{8}$$

such that

$$|\lambda| \leq 1 \tag{9}$$

for stability. Substituting (8) into (5-7), we obtain

$$\mathbf{J}\mathbf{x} = 0 \tag{10}$$

where

$$\mathbf{x_1} = \left[\, p_p^{n+\frac{1}{2}} \quad u^{n+\frac{1}{2}} \quad p^{n+\frac{1}{2}} \quad \dot{p}^{n+\frac{1}{2}} \quad p^n \quad \dot{p}^n \,\right]^T$$

$$\mathbf{x_2} = \left[\, z_p^{n+\frac{1}{2}} \quad \gamma^{n+\frac{1}{2}} \quad q^{n+\frac{1}{2}} \quad \dot{q}^{n+\frac{1}{2}} \quad q^n \quad \dot{q}^n \,\right]^T$$

$$\mathbf{J} = \begin{bmatrix} \mathbf{J}_{11} & \mathbf{J}_{12} \\ \mathbf{J}_{21} & \mathbf{J}_{22} \end{bmatrix} \tag{11}$$

40

$$\mathbf{J}_{11} = \begin{bmatrix} 1 & 0 & 0 & 0 & -1 & -\delta \\ \left(\eta\omega^2 - \delta\zeta\omega^3\right) & \left(1 + \delta\zeta\omega\right) & 0 & 0 & 0 & \zeta\omega \\ 0 & -\delta^2 & \left(1 + \delta^2\omega^2\right) & 0 - 1 & -\delta \\ 0 & 0 & -\frac{1}{\delta} & 1 & \frac{1}{\delta} & 0 \\ 0 & 0 & -2 & \lambda + 1 & 0 \\ 0 & 0 & 0 & -2 & 0 & \lambda + 1 \end{bmatrix} \tag{12}$$

$$\mathbf{J}_{12} = \begin{bmatrix} 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & \delta\zeta\xi\omega & 0 & 0 & 0 & 0 \\ 0 & -\delta^2\xi & 0 & 0 & 0 & 0 \\ 0 & -\delta\xi & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix} \tag{13}$$

$$\mathbf{J}_{21} = \begin{bmatrix} 0 & 0 & 0 & 0 & 0 & 0 \\ -\delta\omega^2 & \delta & 0 & 0 & 0 & 1 \\ 0 & -\delta^2 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix} \tag{14}$$

$$\mathbf{J}_{22} = \begin{bmatrix} 1 & 0 & 0 & 0 & 0 & -1 \\ -1 & \left(1 + \delta\xi\right) & 0 & 0 & 0 & 0 \\ 0 & 0 & \left(1 + \delta^2\omega^2\right) & 0 & -1 & -\delta \\ 0 & 0 & -\frac{1}{\delta} & 1 & \frac{1}{\delta} & 0 \\ 0 & 0 & -2 & 0 & \lambda + 1 & 0 \\ 0 & 0 & 0 & -2 & 0 & \lambda + 1 \end{bmatrix} \tag{15}$$

A nontrivial solution to (10) is found from

$$\det \mathbf{J} = 0 \tag{16}$$

which leads to the characteristic equation

$$\begin{aligned} &\left(\left(1 - \delta\xi\right)\left(1 + \delta^3\zeta\omega^3 - \delta^2\eta\omega^2\right) + \delta\xi\left(1 + \delta^2\omega^2\right)\right)z^4 \\ &\quad + \left(\delta\zeta\omega\left(1 - \delta\xi\right) + \delta\xi\left(1 + \delta^3\zeta\omega^3 - \delta^2\eta\omega^2\right)\right)z^3 \\ &\left(\left(1 - \delta\xi\right)\left(\delta^2\omega^2 + \delta^2\eta\omega^2\right) + \delta^2\omega^2\left(1 + \delta^3\zeta\omega^3 - \delta^2\eta\omega^2\right)\right. \\ &\qquad\qquad \left. + \delta\xi\left(\delta\zeta\omega + \delta^2\omega^2 + \delta^4\omega^4\right)\right)z^2 \\ &\left(\delta^2\omega^2\left(\delta\zeta\omega\right) + \delta\xi\left(\delta^2\omega^2 + \delta^2\eta\omega^2\right)\right)z \\ &\qquad\qquad + \delta^2\omega^2\left(\delta^2\omega^2 + \delta^2\eta\omega^2\right) = 0 \end{aligned} \tag{17}$$

where

$$\lambda = \frac{1+z}{1-z}, \quad |\lambda| \le 1 \quad \Longleftrightarrow \quad Re(z) \le 0 \qquad (18)$$

Thus, a test of the polynomial equation for possible positive real roots by the Routh-Hurwitz criterion indicates that the partitioned approach as applied to the modal equations give a computationally stable solution for no velocity feedback $\zeta = 0$ provided

$$h \le \frac{2}{\sqrt{\eta}\omega} \qquad (19)$$

$$h \le \frac{2}{\xi} \qquad (20)$$

APPENDIX D

ACSIS Source Code

File: Makefile

```
.SUFFIXES:  .f .o

FFLAGS =

.f.o:
        fortran -c $(FFLAGS) $*.f

OBJS  =         acsis.o         acsisout.o      addstf.o        \
                beam3d.o        forces.o        input.o         \
                pmvmul.o        prepfem.o       profile.o       \
                read.o          solver.o        nophlag.o       \
                zerovect.o      lu.o            prepcon.o       \
                control.o       secorder.o      measure.o       \
                eigens.o        singeig.o       animout.o       \
                stiffrc.o       estifvm.o       renum.o         \
                kfilter.o

acsis.exe:      $(OBJS)
        fortran -o acsis.exe $(FFLAGS) $(OBJS)
```

File: shared.inc

```
C
C     ------------------------------------------------------------------
C
C     shared.inc (ACSIS database)
C
C     ------------------------------------------------------------------
C
C
C     Argument definitions:
C       adamp:    Rayleigh damping coefficient alpha
C       b:        actuator location matrix (packed storage)
C       brow:     row number of corresponding real value in b
C       bcol:     column number of corresonding real value in b
C       bval:     number of nonzero values in b
C       bdamp:    Rayleigh damping coefficient beta
C       confile:  controller input file name
C       contype:  id for type of control
C       coxyz:    array of the x,y, and z components of each node
C       delta:    one-half time step
C       delsq:    one-half time step squared
C       ec:       control prediction integration coefficient matrix
C       emat:     array of element material types
C       eo:       observer construct matrix S in vector form
C       eprop:    array of element property types
C       es:       structure construct matrix S (M+delta*D+delsq*K)
C       etype:    array of element types
C       elnum:    array of element numbers for domain decomposition
C       f:        vector of applied forces
C       f1:       control gain matrix
```

```
C       f2:       control gain matrix
C       femfile:  finite element input file name
C       forceid:  identification number of forcing function
C       gamma:    state correction force
C       gc:       RHS vector for control prediction module
C       gk:       RHS vector for Kalman filter momentum eqn
C       go:       RHS vector for observer module
C       gs:       RHS vector for structure module
C       h:        time step size
C       hd:       displacement sensor location matrix (packed storage)
C       hdrow:    row number of corresponding real value in hd
C       hdcol:    column number of corresonding real value in hd
C       hdval:    number of nonzero values in hd
C       hv:       velocity sensor location matrix (packed storage)
C       hvrow:    row number of corresponding real value in hv
C       hvcol:    column number of corresonding real value in hv
C       hvval:    number of nonzero values in hv
C       id:       DOF mapping array: id(comp,node #)=Global DOF #
C       ix:       array of element connectivity and orientation
C       inertia:  array of concentrated inertias or lumped masses
C       jdiag:    array of diagonal element addresses
C       l1:       State estimator filter gain matrix
C       l2:       State estimator filter gain matrix
C       mask:
C       mass:     mass matrix M in reduced vector form
C       mat:      array of different materials
C       mlen:     length of global matrices in profile vector storage
C       nact:     actual number of actuators
C       ncsi:     actual number of actuators and sensors
C       ndisout:  number of displacement results to output
C       ndof:     actual number of degrees of freedom
C       ndomain:  actual number of element domains (for dom. decomp.)
C       nel:      actual number of elements
C       neld:     array of number of elements in each domain
C       nnp:      actual number of nodes
C       nsen:     actual number of sensors
C       nvelout:  number of velocity results to output
C       nolag:    logical flag to signal corrector loop in measurement
C       outfile:  output file name
C       outlabel: array of output data requested
C       pin:      array of element pin release codes
C       pivot:    Column pivoting info from FACTA
C       prop:     array of different properties
C       q:        generalized displacement vector
C       q0:       initial displacement condition
C       qalpha:   gain scale factor for f1
C       qalphao:  gain scale factor for l1
C       qbeta:    gain scale factor for f2
C       qbetao:   gain scale factor for l2
C       qdot:     velocity vector
C       qdot0:    initial velocity condition
C       qe:       state estimator displacement vector
C       qedot:    state estimator velocity vector
C       r:        Solution vector of control module {u,gamma}
C       scalef:   Scaling factor for forcing function
C       stiff:    stiffness matrix K in reduced vector form
C       t0:       initial time
C       tc        control-on time
C       tf:       final time
```

45

```
c      u:          vector of control forces
c
c      Parameter definitions
c        MAXACT:   max. # of actuators
c        MAXCSI:   max. combined # of actuators and sensors
c        MAXDAT:   max. # of materials and properties
c        MAXDOF:   max. # of degrees of freedom
c        MAXDOM:   max. # of decomposition domains
c        MAXELE:   max. # of elements
c        MAXMLEN:  max. length of global vectors in reduced form
c        MAXNODE:  max. # of nodes
c

       parameter(MAXDOF=3000, MAXACT=50, MAXCSI=100)
       parameter(MAXNODE=1000, MAXELE=3000, MAXDAT=100)
       parameter(MAXMLEN=200000, MAXDOM=50, MAXNZV=200)

       real*8 t0,tf,tc,h,delta,delsq,qalpha,qbeta,qalphao,qbetao
       real*8 q(MAXDOF),qdot(MAXDOF),qe(MAXDOF),qedot(MAXDOF)
       real*8 u(MAXACT),gamma(MAXACT),f(MAXDOF),r(MAXCSI)
       real*8 es(MAXMLEN),eo(MAXMLEN),ec(MAXCSI,MAXCSI)
       real*8 gs(MAXDOF),go(MAXDOF),gc(MAXCSI),scalef,pe(MAXDOF)
       real*8 mass(MAXMLEN),stif(MAXMLEN),adamp,bdamp,gk(MAXDOF)
       real*8 coxyz(3,MAXNODE),mat(6,MAXDAT),prop(10,MAXDAT)
       real*8 q0(6,MAXNODE),qdot0(6,MAXNODE),inertia(6,MAXNODE)
       real*8 b(MAXNZV),hd(MAXNZV),hv(MAXNZV),estifm(78,500)
       real*8 f1(MAXACT,MAXDOF),f2(MAXACT,MAXDOF)
       real*8 l1(MAXDOF,MAXACT),l2(MAXDOF,MAXACT)
       integer etype(MAXELE),ix(4,MAXELE),emat(MAXELE),forceid
       integer eprop(MAXELE),pin(6,MAXELE),id(6,MAXNODE)
       integer mask(MAXNODE),contype,brow(MAXNZV),bcol(MAXNZV)
       integer hdrow(MAXNZV),hdcol(MAXNZV),hvrow(MAXNZV)
       integer hvcol(MAXNZV),bval,hdval,hvval
       integer ndof,nact,nsen,ncsi,mlen,jdiag(MAXDOF),nnp,nel,neig
       integer neld(MAXDOM),elnum(MAXELE,MAXDOM),eldom(MAXELE),ndomain
       integer outlabel(40),ndisout,nvelout,pivot(MAXCSI)
       integer iadjcy(MAXMLEN),icount(MAXNODE+1),perm(MAXNODE)
       integer xls(MAXNODE)
       logical animate,nolag
       character*32 femfile,confile,outfile,animfile

       COMMON /FILES/ femfile,confile,outfile,outlabel,ndisout,
      .               nvelout,animfile,animate,nolag
       COMMON /TIMERS/ t0,tf,tc,h,delta,delsq
       COMMON /STATES/ q,qdot,qe,qedot,u,gamma,f,r,pe
       COMMON /FEMDAT/ mass,stif,adamp,bdamp,coxyz,mat,prop,q0,qdot0,
      .               inertia,scalef
       COMMON /INTEGR/ es,eo,ec,gs,go,gc,gk,pivot
       COMMON /DIMENS/ ndof,nact,nsen,ncsi,mlen,jdiag,nnp,nel,neig
       COMMON /CONDAT/ b,hd,hv,f1,f2,l1,l2,
      .               qalpha,qbeta,qalphao,qbetao
       COMMON /ELEDOM/ estifm,ndomain,neld,elnum,eldom
       COMMON /INTGER/ forceid,etype,ix,emat,eprop,pin,id,mask,
      .               contype,brow,bcol,hdrow,hdcol,hvrow,hvcol,
      .               bval,hdval,hvval
       COMMON /RESEQN/ iadjcy,icount,perm,xls
```

File: acsis.f

```
C=Program ACSIS
C=Purpose Accelerated CSI Simulation
C=Author K. Alvin
C=Date May 1990
C=Block Fortran
C-----------------------------------------------------------------------C
C                                                                        C
C      program ACSIS                                                     C
C                                                                        C
C                                                                        C
C      Purpose:   2nd Order Accelerated CSI Simulation                   C
C                                                                        C
C                                                                        C
C-----------------------------------------------------------------------C

       program ACSIS

C      GET SHARED DATA FILE

       include 'shared.inc'

C      LOCAL VARIABLES

       real*8 t,z(MAXACT)

       integer n,m,runtype,outskip

C      LOGIC

       call INPUT(runtype,outskip)

       if (runtype) 100,200,300

C      EIGENMODE ANALYSIS

100    continue
       call PREPFEM
       call EIGENS
       goto 999

C      CSI SIMULATION

200    call PREPFEM
       call PREPCON

       n = 0
       m = 0
       print *,'Finished Preprocessing . . . starting simulation'
       print *,'Time =',t0
       CALL ACSISOUT(t0)

       do 250 t=t0,tf,h

         call FORCES(t+h/2)

C      Predict CSI coupling variables u and gamma
```

47

```
          if (t .ge. tc) then
            call MEASURE(z)
            call CONTROL(z)
            if (nolag) then
              call NOPHLAG(z)
              call CONTROL(z)
              endif
            endif

C     Structure and observer set up for parallel execution

CVD$  CNCALL
          do 275 i=1,2

C     Integrate Observer Equations

          if ((i .eq. 1).and.(t .ge. tc)) then
            if (contype .eq. 0) then
              call SECORDER(mass,stif,adamp,bdamp,f,go,eo,qe,qedot,
     &                delta,delsq,jdiag,ndof,MAXDOF)
            elseif (contype .eq. 1) then
              call KFILTER
              endif

C     Integrate Structure Equations

          elseif (i .eq. 2) then
            call SECORDER(mass,stif,adamp,bdamp,f,gs,es,q,qdot,
     &                delta,delsq,jdiag,ndof,MAXDOF)
            endif

275       continue

C     PRINT TIME EACH 100 iterations

          n = n + 1
          m = m + 1
          if (n .ge. 100) then
            print *, 'Time = ',t+h
            n = 0
            endif
          if (m .ge. outskip) then
            call ACSISOUT(t+h)
            write(24,'(40f12.8)') t,(z(i),i=1,nsen)
            m = 0
            endif

250       continue
          goto 999

C     TRANSIENT RESPONSE

300   call PREPFEM

          n = 0
          m = 0
          print *,'Finished Preprocessing . . . . starting simulation'
          print *,'Time = ',t0
```

```
      call ACSISOUT(t0)

      do 350 t=t0,tf,h

        call FORCES(t+h/2)

        call ZEROVECT(gs,ndof)

        call SECORDER(mass,stif,adamp,bdamp,f,gs,es,q,qdot,
     *               delta,delsq,jdiag,ndof,MAXDOF)

C     PRINT TIME EACH 100 iterations

        n = n + 1
        m = m + 1
        if (n .ge. 100) then
          print *,'Time = ',t+h
          n = 0
        endif
        if (m .ge. outskip) then
           call ACSISOUT(t+h)
           m = 0
           endif

350   continue

999   stop
      end
```

File: acsisout.f

```
C=Module ACSISOUT
C=Purpose Write desired output from ACSIS for plotting, etc.
C=Author K. Alvin
C=Date May 1990
C=Block Fortran
C  -----------------------------------------------------------------
C
C     Subroutine ACSISOUT
C
C     Purpose:
C         This subroutine outputs formatted displacement and velocity
C         results at a given time for plotting time histories. The
C         desired output variables are defined in outlabel().
C
C  -----------------------------------------------------------------
C
C     Arguments
C       t  -  time
C

      subroutine ACSISOUT(t)

      include 'shared.inc'
      real*8 t
```

49

```
C      LOCAL VARIABLES

       integer i

C      LOGIC

       write(13,'(40f12.8)') t,(q(id(outlabel(i+10),outlabel(i))),
      . i=1,ndisout),(qdot(id(outlabel(i+30),outlabel(i+20)))),
      . i=1,nvelout)

       write(23,'(40f12.8)') t,(qa(id(outlabel(i+10),outlabel(i))),
      . i=1,ndisout),(qedot(id(outlabel(i+30),outlabel(i+20)))),
      . i=1,nvelout)

       write(25,'(40f12.8)') t,(u(i),i=1,nact),(gamma(i),i=1,nsen)

       if (animate) call ANIMOUT(q,id,nnp,t,15)

       return
       end
```

File: addstf.f

```
C=Module ADDSTF
C=Purpose Assemble Global stiffness matrix
C=Author who knows
C=Update January 1989, by E. Pramono
C=Block Portran
       subroutine ADDSTF(sk,lm,bk,jdiag,nseq)
C+-------------------------------------------------------------+C
C      PURPOSE:                                                 C
C          THIS SUBROUTINE ASSEMBLES THE ELEMENT STIFFNESS MATRICES  C
C          INTO THE COMPACTED GLOBAL STIFFNESS VECTOR.          C
C                                                               C
C      ARGUMENTS:                                               C
C          sk    - ELEMENT STIFFNESS MATRIX                     C
C          lm    - LOCATION VECTOR FOR ELEMENT STIFFNESS MATRIX  C
C          bk    - COMPACTED GLOBAL STIFFNESS VECTOR            C
C          jdiag - VECTOR OF DIAGONAL ELEMENT ADDRESSES         C
C          nseq  - NUMBER OF DEGREES OF FREEDOM PER ELEMENT     C
C-------------------------------------------------------------C

C    ARGUMENTS

       real*8 sk(nseq,nseq), bk(1)
       integer lm(18), jdiag(1)
C      integer lm(18), jdiag(1), nseq

C    LOCAL ARGUMENTS

       integer i, j, k, l, m

C    ASSEMBLE GLOBAL STIFFNESS AND LOAD ARRAYS

       do 20 j = 1, nseq
          k = lm(j)
          if (k .eq. 0) goto 20
```

```
           l = jdiag(k) - k
C          l = jdiag(k+1) - k
           do 10 i = 1, nseq
              m = lm(i)
              if(m .gt. k .OR. m .eq. 0) goto 10
              m = l + m
              bk(m) = bk(m) + sk(i,j)
10         continue
20      continue
C
        return
        end
C=End Fortran
```

File: beam3d.f

```
C=Module BEAM3D
C=Purpose Construct 3-d Timoshenko beam element stiffness and lumped mass
C=Author K. Alvin
C=Date May 1990
C=Block Fortran
        subroutine BEAM3D(n,ni,nj,nk,xyz,emod,gmod,rho,area,ssf2,ssf3,
     &                 jtor,i2,i3,ipin,sk,sm)

C  ARGUMENTS:
C
C      n       Element ID Number
C      ni      Node ID Number at End i
C      nj      Node ID Number at End j
C      xyz     Node Location Array
C      emod    Material Elastic Modulus (Young's Modulus)
C      gmod    Material Modulus of Rigidity (Shear Modulus)
C      rho     Material Mass Density
C      area    Element Cross-sectional area
C      ssf2    Shear shape factor in element x2 direction
C      ssf3    Shear shape factor in element x3 direction
C      jtor    Torsional constant J
C      i2      Area moment of inertia about element x2 axis
C      i3      Area moment of inertia about element x3 axis
C      ipin    Pin release codes: 0=Fixed, 1=Freed
C              (1)     Axial
C              (2)     Torsional
C              (3)     End A rotation about x2 axis
C              (4)     End A rotation about x3 axis
C              (5)     End B rotation about x2 axis
C              (6)     End B rotation about x3 axis
C      sk      Element Stiffness Matrix
C      sm      Element Mass Matrix

        integer n,ni,nj,nk,ipin(1)
        real*8  xyz(3,1),emod,gmod,rho,area,ssf2,ssf3,jtor,i2,i3
        real*8  sk(12,1),sm(12,1)

C  LOCAL VARIABLES:

        integer i,j
        real*8  dc(3,3),length,rlength,kc(10),mc(3)
```

51

```
C   LOGIC

C   Find Element Length

      length = 0.0d0
      do 10 i = 1,3
        dc(1,i) = xyz(i,nj) - xyz(i,ni)
        length = length + dc(1,i)**2
10      continue
      length = sqrt(length)
      if (length .eq. 0.0d0) then
        print *, 'BAR2D: Zero element length; n= ',n
        return
        endif

C   Find direction cosines for x1,x2,x3 element axes

      do 15 i=1,3
        dc(1,i) = dc(1,i)/length
        if (nk .eq. 0) then
          dc(2,i) = 0.0
        else
          dc(2,i) = xyz(i,nk) - xyz(i,ni)
          endif
15      continue
      if (nk .eq. 0) dc(2,3) = 1.0
16    dc(3,1) = dc(1,2)*dc(2,3) - dc(2,2)*dc(1,3)
      dc(3,2) = dc(2,1)*dc(1,3) - dc(1,1)*dc(2,3)
      dc(3,3) = dc(1,1)*dc(2,2) - dc(2,1)*dc(1,2)
      rlength = sqrt(dc(3,1)**2 + dc(3,2)**2 + dc(3,3)**2)
      if (rlength .ne. 0.) goto 17
      dc(2,2) = 1.0
      dc(2,3) = 0.0
      goto 16

17    do 18 i=1,3
        dc(3,i) = dc(3,i)/rlength
18      continue
      dc(2,1) = dc(3,2)*dc(1,3) - dc(1,2)*dc(3,3)
      dc(2,2) = dc(1,1)*dc(3,3) - dc(3,1)*dc(1,3)
      dc(2,3) = dc(3,1)*dc(1,2) - dc(1,1)*dc(3,2)

C   Compute various stiffness constants, accounting for pin codes

      if (ipin(1) .eq. 0) then
        kc(1) = area*emod/length
      else
        kc(1) = 0.0d0
        endif

      if (ipin(4) .eq. 0) then
        if (ipin(6) .eq. 0) then
          kc(2) = area*gmod*ssf2/length
          kc(6) = i3*emod/length
          kc(7) = kc(2)*length/2.0d0
          kc(9) = kc(7)*length/2.0d0
        else
          print *,'BEAM3D: Pin code error, x3 direction, el #',n
```

52

```
        endif
else
  if (ipin(6) .eq. 0) then
    print *,'BEAM3D: Pin code error, x3 direction, el #',n
  else
    kc(2) = 0.0d0
    kc(6) = 0.0d0
    kc(7) = 0.0d0
    kc(9) = 0.0d0
    endif
  endif

if (ipin(3) .eq. 0) then
  if (ipin(5) .eq. 0) then
    kc(3) = area*gmod*ssf3/length
    kc(5) = i2*emod/length
    kc(8) = kc(3)*length/2.0d0
    kc(10) = kc(8)*length/2.0d0
  else
    print *,'BEAM3D: Pin code error, x2 direction, el #',n
    endif
else
  if (ipin(5) .eq. 0) then
    print *,'BEAM3D: Pin code error, x2 direction, el #',n
  else
    kc(3) = 0.0d0
    kc(5) = 0.0d0
    kc(8) = 0.0d0
    kc(10) = 0.0d0
    endif
  endif

if (ipin(2) .eq. 0) then
  kc(4) = jtor*gmod/length
else
  kc(4) = 0.0d0
  endif

mc(1) = area*rho*length/2.0d0
mc(2) = i2*rho*length/2.0d0
mc(3) = i3*rho*length/2.0d0

sk(1,1)    = kc(1)*dc(1,1)*dc(1,1) + kc(2)*dc(2,1)*dc(2,1) +
             kc(3)*dc(3,1)*dc(3,1)
sk(1,2)    = kc(1)*dc(1,1)*dc(1,2) + kc(2)*dc(2,1)*dc(2,2) +
             kc(3)*dc(3,1)*dc(3,2)
sk(1,3)    = kc(1)*dc(1,1)*dc(1,3) + kc(2)*dc(2,1)*dc(2,3) +
             kc(3)*dc(3,1)*dc(3,3)
sk(1,4)    = kc(7)*dc(2,1)*dc(3,1) - kc(8)*dc(3,1)*dc(2,1)
sk(1,5)    = kc(7)*dc(2,1)*dc(3,2) - kc(8)*dc(3,1)*dc(2,2)
sk(1,6)    = kc(7)*dc(2,1)*dc(3,3) - kc(8)*dc(3,1)*dc(2,3)
sk(1,7)    = -sk(1,1)
sk(1,8)    = -sk(1,2)
sk(1,9)    = -sk(1,3)
sk(1,10)   = sk(1,4)
sk(1,11)   = sk(1,5)
sk(1,12)   = sk(1,6)
sk(2,2)    = kc(1)*dc(1,2)*dc(1,2) + kc(2)*dc(2,2)*dc(2,2) +
             kc(3)*dc(3,2)*dc(3,2)
```

53

```
sk(2,3)    =  kc(1)*dc(1,2)*dc(1,3) + kc(2)*dc(2,2)*dc(2,3) +
              kc(3)*dc(3,2)*dc(3,3)
sk(2,4)    =  kc(7)*dc(2,2)*dc(3,1) - kc(8)*dc(3,2)*dc(2,1)
sk(2,5)    =  kc(7)*dc(2,2)*dc(3,2) - kc(8)*dc(3,2)*dc(2,2)
sk(2,6)    =  kc(7)*dc(2,2)*dc(3,3) - kc(8)*dc(3,2)*dc(2,3)
sk(2,7)    = -sk(1,2)
sk(2,8)    = -sk(2,2)
sk(2,9)    = -sk(2,3)
sk(2,10)   =  sk(2,4)
sk(2,11)   =  sk(2,5)
sk(2,12)   =  sk(2,6)
sk(3,3)    =  kc(1)*dc(1,3)*dc(1,3) + kc(2)*dc(2,3)*dc(2,3) +
              kc(3)*dc(3,3)*dc(3,3)
sk(3,4)    =  kc(7)*dc(2,3)*dc(3,1) - kc(8)*dc(3,3)*dc(2,1)
sk(3,5)    =  kc(7)*dc(2,3)*dc(3,2) - kc(8)*dc(3,3)*dc(2,2)
sk(3,6)    =  kc(7)*dc(2,3)*dc(3,3) - kc(8)*dc(3,3)*dc(2,3)
sk(3,7)    = -sk(1,3)
sk(3,8)    = -sk(2,3)
sk(3,9)    = -sk(3,3)
sk(3,10)   =  sk(3,4)
sk(3,11)   =  sk(3,5)
sk(3,12)   =  sk(3,6)
sk(4,4)    =  kc(4)*dc(1,1)*dc(1,1)+(kc(10)+kc(5))*dc(2,1)*dc(2,1)
            + (kc(9)+kc(6))*dc(3,1)*dc(3,1)
sk(4,5)    =  kc(4)*dc(1,1)*dc(1,2)+(kc(10)+kc(5))*dc(2,1)*dc(2,2)
            + (kc(9)+kc(6))*dc(3,1)*dc(3,2)
sk(4,6)    =  kc(4)*dc(1,1)*dc(1,3)+(kc(10)+kc(5))*dc(2,1)*dc(2,3)
            + (kc(9)+kc(6))*dc(3,1)*dc(3,3)
sk(4,7)    = -sk(1,4)
sk(4,8)    = -sk(2,4)
sk(4,9)    = -sk(3,4)
sk(4,10)   = -kc(4)*dc(1,1)*dc(1,1)+(kc(10)-kc(5))*dc(2,1)*dc(2,1)
            + (kc(9)-kc(6))*dc(3,1)*dc(3,1)
sk(4,11)   = -kc(4)*dc(1,1)*dc(1,2)+(kc(10)-kc(5))*dc(2,1)*dc(2,2)
            + (kc(9)-kc(6))*dc(3,1)*dc(3,2)
sk(4,12)   = -kc(4)*dc(1,1)*dc(1,3)+(kc(10)-kc(5))*dc(2,1)*dc(2,3)
            + (kc(9)-kc(6))*dc(3,1)*dc(3,3)
sk(5,5)    =  kc(4)*dc(1,2)*dc(1,2)+(kc(10)+kc(5))*dc(2,2)*dc(2,2)
            + (kc(9)+kc(6))*dc(3,2)*dc(3,2)
sk(5,6)    =  kc(4)*dc(1,2)*dc(1,3)+(kc(10)+kc(5))*dc(2,2)*dc(2,3)
            + (kc(9)+kc(6))*dc(3,2)*dc(3,3)
sk(5,7)    = -sk(1,5)
sk(5,8)    = -sk(2,5)
sk(5,9)    = -sk(3,5)
sk(5,10)   =  sk(4,11)
sk(5,11)   = -kc(4)*dc(1,2)*dc(1,2)+(kc(10)-kc(5))*dc(2,2)*dc(2,2)
            + (kc(9)-kc(6))*dc(3,2)*dc(3,2)
sk(5,12)   = -kc(4)*dc(1,2)*dc(1,3)+(kc(10)-kc(5))*dc(2,2)*dc(2,3)
            + (kc(9)-kc(6))*dc(2,3)*dc(3,3)
sk(6,6)    =  kc(4)*dc(1,3)*dc(1,3)+(kc(10)+kc(5))*dc(2,3)*dc(2,3)
            + (kc(9)+kc(6))*dc(3,3)*dc(3,3)
sk(6,7)    = -sk(1,6)
sk(6,8)    = -sk(2,6)
sk(6,9)    = -sk(3,6)
sk(6,10)   =  sk(4,12)
sk(6,11)   =  sk(5,12)
sk(6,12)   = -kc(4)*dc(1,3)*dc(1,3)+(kc(10)-kc(5))*dc(2,3)*dc(2,3)
            + (kc(9)-kc(6))*dc(3,3)*dc(3,3)
sk(7,7)    =  sk(1,1)
```

```fortran
      sk(7,8)    =  sk(1,2)
      sk(7,9)    =  sk(1,3)
      sk(7,10)   = -sk(1,4)
      sk(7,11)   = -sk(1,5)
      sk(7,12)   = -sk(1,6)
      sk(8,8)    =  sk(2,2)
      sk(8,9)    =  sk(2,3)
      sk(8,10)   = -sk(2,4)
      sk(8,11)   = -sk(2,5)
      sk(8,12)   = -sk(2,6)
      sk(9,9)    =  sk(3,3)
      sk(9,10)   = -sk(3,4)
      sk(9,11)   = -sk(3,5)
      sk(9,12)   = -sk(3,6)
      sk(10,10)  =  sk(4,4)
      sk(10,11)  =  sk(4,5)
      sk(10,12)  =  sk(4,6)
      sk(11,11)  =  sk(5,5)
      sk(11,12)  =  sk(5,6)
      sk(12,12)  =  sk(6,6)

      do 50 i = 1,12
        do 55 j = 1,12
          sm(i,j) = 0.d0
55        continue
50      continue


C  Row-sum rotated mass matrix to re-diagonalize

      sm(1,1)    =  mc(1)
      sm(2,2)    =  mc(1)
      sm(3,3)    =  mc(1)
      sm(4,4)    =  mc(2)*(dc(1,1)*dc(1,1)+dc(2,1)*dc(2,1)) +
                    mc(3)*(dc(1,1)*dc(1,1)+dc(3,1)*dc(3,1)) +
                    mc(2)*(dc(1,1)*dc(1,2)+dc(2,1)*dc(2,2)) +
                    mc(3)*(dc(1;1)*dc(1,2)+dc(3,1)*dc(3,2)) +
                    mc(2)*(dc(1,1)*dc(1,3)+dc(2,1)*dc(2,3)) +
                    mc(3)*(dc(1,1)*dc(1,3)+dc(3,1)*dc(3,3))
C     sm(4,5)    =  mc(2)*(dc(1,1)*dc(1,2)+dc(2,1)*dc(2,2)) +
C                   mc(3)*(dc(1,1)*dc(1,2)+dc(3,1)*dc(3,2))
C     sm(4,6)    =  mc(2)*(dc(1,1)*dc(1,3)+dc(2,1)*dc(2,3)) +
C                   mc(3)*(dc(1,1)*dc(1,3)+dc(3,1)*dc(3,3))
C     sm(5,4)    =  mc(2)*(dc(1,1)*dc(1,2)+dc(2,1)*dc(2,2)) +
C                   mc(3)*(dc(1,1)*dc(1,2)+dc(3,1)*dc(3,2))
      sm(5,5)    =  mc(2)*(dc(1,2)*dc(1,2)+dc(2,2)*dc(2,2)) +
                    mc(3)*(dc(1,2)*dc(1,2)+dc(3,2)*dc(3,2)) +
                    mc(2)*(dc(1,1)*dc(1,2)+dc(2,1)*dc(2,2)) +
                    mc(3)*(dc(1,1)*dc(1,2)+dc(3,1)*dc(3,2)) +
                    mc(2)*(dc(1,2)*dc(1,3)+dc(2,2)*dc(2,3)) +
                    mc(3)*(dc(1,2)*dc(1,3)+dc(3,2)*dc(3,3))
C     sm(5,6)    =  mc(2)*(dc(1,2)*dc(1,3)+dc(2,2)*dc(2,3)) +
C                   mc(3)*(dc(1,2)*dc(1,3)+dc(3,2)*dc(3,3))
C     sm(6,4)    =  mc(2)*(dc(1,1)*dc(1,3)+dc(2,1)*dc(2,3)) +
C                   mc(3)*(dc(1,1)*dc(1,3)+dc(3,1)*dc(3,3))
C     sm(6,5)    =  mc(2)*(dc(1,2)*dc(1,3)+dc(2,2)*dc(2,3)) +
C                   mc(3)*(dc(1,2)*dc(1,3)+dc(3,2)*dc(3,3))
      sm(6,6)    =  mc(2)*(dc(1,3)*dc(1,3)+dc(2,3)*dc(2,3)) +
                    mc(3)*(dc(1,3)*dc(1,3)+dc(3,3)*dc(3,3)) +
```

```
                         mc(2)*(dc(1,1)*dc(1,3)+dc(2,1)*dc(2,3)) +
                         mc(3)*(dc(1,1)*dc(1,3)+dc(3,1)*dc(3,3)) +
                         mc(2)*(dc(1,2)*dc(1,3)+dc(2,2)*dc(2,3)) +
                         mc(3)*(dc(1,2)*dc(1,3)+dc(3,2)*dc(3,3))
         sm(7,7)    =  mc(1)
         sm(8,8)    =  mc(1)
         sm(9,9)    =  mc(1)
         sm(10,10)  =  sm(4,4)
C        sm(10,11)  =  sm(4,5)
C        sm(10,12)  =  sm(4,6)
C        sm(11,10)  =  sm(5,4)
         sm(11,11)  =  sm(5,5)
C        sm(11,12)  =  sm(5,6)
C        sm(12,10)  =  sm(6,4)
C        sm(12,11)  =  sm(6,5)
         sm(12,12)  =  sm(6,6)

         do 100 i=1,12
           do 200 j=1,i-1
             sk(i,j) = sk(j,i)
200          continue
100        continue

         return
         end
C=End Fortran
```

File: forces.f

```
C=Module FORCES
C=Purpose Calculate applied force vector at given time
C=Author K. Alvin
C=Date May 1990
C=Block Fortran
C   ------------------   ------------------------------------------------
C
C      Subroutine FORCES
C
C      Purpose:
C          Returns force from stored function at any given time.
C          The forcing functions are hardwired by the user.  The
C          function is selectable at program excecution using the
C          forcing function ID, which by convention is the statement
C          label used in branching.
C
C   ----------------------------------------------------------------------
C

       subroutine FORCES(time)

       include 'shared.inc'
       real*8 time,pi

C      LOGIC

       pi = 3.1415926
```

```
      call ZEROVECT(f,ndof)

101   if (forceid .eq. 101) then

          if (time .le. .02) then
            f(id(2,15)) = 100.*(1.-cos(2.*pi*time/.02))
          endif

102   elseif (forceid .eq. 102) then

          if (time .lt. .1) then
            f(id(2,95)) = 10.
          elseif (time .eq. .1) then
            f(id(2,95)) = 0.
          elseif ((time .gt. .1).and.(time .lt. .2)) then
            f(id(2,95)) = -10.
          else
            f(id(2,95)) = 0.
          endif

103   elseif (forceid .eq. 103) then

          if (time .le. .01) then
            f(id(1,15)) = 100
          endif

104   elseif (forceid .eq.104) then

          if ((time .gt. 0) .and. (time .lt. .17)) then
            f(id(3,125)) = 10
          elseif ((time .gt. .17) .and. (time .lt. 1.0)) then
            f(id(3,125)) = -10
          endif

105   elseif (forceid .eq. 105) then

          if (time .le. .01) then
            f(id(2,9)) = 100.*(1.-cos(2.*pi*time/.01))
          elseif (time .le. .02) then
            f(id(2,9)) = 100.*(cos(2.*pi*time/.01)-1.)
          endif

      endif

      do 10 i = 1, ndof
        f(i) = scalef * f(i)
10    continue

      return
      end
```

File: input.f

```
C=Module INPUT
C=Purpose Input data parameters for ACSIS
C=Author K. Alvin
```

57

```
C=Date May 1990
C=Block Fortran
C   --------------------------------------------------------------------------
C
C     Subroutine INPUT
C
C
C   --------------------------------------------------------------------------
C
C   Argument definitions
C
C     runtype   -  ID of analysis run type
C     savin     -  variable to control creation of input file
C     runfile   -  variable indicates if run is from input file
C     comment   -  dummy name for comment input lines
C     outskip   -  number of steps to skip before sending output

      subroutine INPUT(runtype,outskip)

      include 'shared.inc'
      integer runtype, outskip
      character*1 savin,runfile,temp
      character*48 comment,inpfile

C     PRINT AND READ START-UP

      print *, '2nd Order Accelerated CSI Simulation (ACSIS)'
      print *
      print *, 'Please input analysis type:'
      print *
      print *, '    1. Eigenmode Analysis'
      print *, '    2. CSI Simulation'
      print *, '    3. Transient Response'
      print *
      read *, runtype

C     RUN OPTIONS AND INPUT FILE SETUP

      runfile = 'n'
      if (runtype .lt. 0) then
         runtype = -1 * runtype
         runfile = 'y'
      endif
      print *, 'Do you wish to save an input file? (y or n)'
      read 21, savin
20    format (a32)
21    format (a1)
      if (savin .eq. 'y') then
         print *, 'Name of save input file? (filename)'
         read 20, inpfile
         open(16,file=inpfile)
         runtype = -1 * runtype
         write(16,'(i2)') runtype
         runtype = -1 * runtype
         write(16,'(a1)')  'n'
         write(16,'(a47)') '* ACSIS input file,two lines above are'
         write(16,'(a48)') '* analysis type and save input file. Do'
         write(16,'(a48)') '* not change them by editing this file.'
      endif
```

58

```
      runtype = runtype - 2

      if (runfile .eq. 'y') then
         do 30 i = 1,4
            read 20, comment
30       continue
      endif
      print *, 'Finite Element Model Input File Name (filename)'
      read 20, femfile
      open(11,file=femfile)
      if (savin .eq. 'y') then
        write(16,'(a47)') '*  Finite element input file?(filename)'
        write(16,'(a32)')  femfile
      endif
      if (runtype) 100,200,300

C     EIGENMODE INPUTS

100   print *,'Number of modes desired:'
      if (runfile .eq. 'y') read 20, comment
      read *, neig
      if (runfile .eq. 'y') read 20, comment
      print *,'Output File Name:'
      read 20, outfile
      open(13,file=outfile)
      if (savin .eq. 'y') then
        write(16,'(a35)') '*  Number of modes desired?'
        write(16,'(i4)') neig
        write(16,'(a33)') '*  Output file?(filename)'
        write(16,'(a32)')  outfile
      endif

      call READFEM

      goto 1000

C     CSI INPUTS

200   print *,'Controller Definition File Name:'
      if (runfile .eq. 'y') read 20, comment
      read 20, confile
      open(12,file=confile)
      print *, 'Please input type of control:'
      print *
      print *, '    1. Full State Feedback'
      print *, '    2. Luenberger Observer (L1=0)'
      print *, '    3. Kalman Filter'
      print *
      if (runfile .eq. 'y') read 20, comment
      read *, contype
      contype = contype - 2
      print *,'Initial time, final time, control-on time, step size:'
      if (runfile .eq. 'y') read 20, comment
      read *, t0,tf,tc,h
      print *,'Forcing function ID, scale factor, damping coeff- a,b:'
      if (runfile .eq. 'y') read 20, comment
      read *, forceid,scalef,adamp,bdamp
      print *,'Phase lag fix?(y or n):'
      if (runfile .eq. 'y') read 20, comment
```

59

```fortran
      read 21, temp
      if (temp .eq. 'y') nolag = .true.
      if (temp .eq. 'n') nolag = .false.
      print *,'Gain scale factors (4 total):'
      if (runfile .eq. 'y') read 20, comment
      read *,qalpha,qbeta,qalphao,qbetao
      if (savin .eq. 'y') then
        write(16,'(a42)') '* Controller file name?(filename)'
        write(16,'(a32)')  confile
        write(16,'(a42)') '* Please input type of control:   '
        write(16,'(i10)')  contype + 2
        write(16,'(a46)') '* Initial,final,control-on,step size?'
        write(16,'(4f14.8)') t0,tf,tc,h
        write(16,'(a49)') '* Forcing function,scale f, damping a,b?'
        write(16,'(i4,f15.6,2f12.8)')  forceid,scalef,adamp,bdamp
        write(16,'(a32)') '* Phase lag fix?(y or n)'
        if (nolag) write(16,'(a1)') 'y'
        if (.not. nolag) write(16,'(a1)') 'n'
        write(16,'(a40)') '* Gain scale factors (4 total)?'
        write(16,'(4f14.8)') qalpha,qbeta,qalphao,qbetao
      endif

      call READFEM

      goto 999

C     TRANSIENT RESPONSE INPUTS

300   print *,'Initial time, final time, step size:'
      if (runfile .eq. 'y') read 20, comment
      read *, t0,tf,h
      print *,'Forcing function ID, scale factor, damping coeff- a,b:'
      if (runfile .eq. 'y') read 20, comment
      read *, forceid,scalef,adamp,bdamp
      if (savin .eq. 'y') then
        write(16,'(a48)') '* Initial, final, step size?'
        write(16,'(3f14.8)') t0,tf,h
        write(16,'(a49)') '* Forcing function,scale f, damping a,b?'
        write(16,'(i4,f15.6,2f12.8)')  forceid,scalef,adamp,bdamp
      endif

      call READFEM

      goto 999

C     OUTPUT OPTIONS

999   print *,'Output File Name:'
      if (runfile .eq. 'y') read 20, comment
      read 20, outfile
      open(13,file=outfile)
      print *,'Number of displacement results to output (max 10):'
      if (runfile .eq. 'y') read 20, comment
      read *,ndisout
      do 500 i=1,ndisout
        print *,'Input node #, dof for displacement output#',i
        read *,outlabel(i),outlabel(i+10)
500     continue
      print *,'Number of velocity results to output (max 10):'
```

```
      if (runfile .eq. 'y')  read 20, comment
      read *,nvelout
      do 600 i=1,nvelout
        print *,'Input node #, dof for velocity output#',i
        read *,outlabel(i+20),outlabel(i+30)
600   continue
      print *,'Send output every how many steps?'
      if (runfile .eq. 'y')  read 20, comment
      read *, outskip
      if (savin .eq. 'y') then
        write(16,'(a38)') '*  Output file name?(filename)'
        write(16,'(a32)')  outfile
        write(16,'(a42)') '*  Number of displacement outputs?'
        write(16,'(i4)')  ndisout
        do 650 i=1,ndisout
          write(16,'(2i8)') outlabel(i),outlabel(i+10)
650     continue
        write(16,'(a38)') '*  Number of velocity outputs?'
        write(16,'(i4)')  nvelout
        do 660 i=1,nvelout
          write(16,'(2i8)') outlabel(i+20),outlabel(i+30)
660     continue
        write(16,'(a44)') '*  Send output every how many steps?'
        write(16,'(i3)')  outskip
      endif

C     ANIMATION OPTION

      print *,'Animation Output? (y or n):'
      if (runfile .eq. 'y')  read 20, comment
      read 21, temp
      if (temp .eq. 'y') animate = .true.
      if (temp .eq. 'n') animate = .false.
      if (animate) then
        print*,'Animation file name (filename)'
        if (runfile .eq. 'y')  read 20, comment
        read 20, animfile
        open (15, file=animfile)
      endif
      if (savin .eq. 'y') then
        write(16,'(a41)') '*  Send animation output?(y or n)'
        if (animate) write(16,'(a1)') 'y'
        if (.not. animate) write(16,'(a1)') 'n'
        if (animate) then
          write(16,'(a31)') '*  Animation file name?'
          write(16,'(a32)')  animfile
        endif
      endif

      delta = h/2.
      delsq = delta**2

1000  return
      end
```

File: pmvmul.f

```
C=Module PMVMUL
C=Author K. Alvin
C=Date May 1990
C=Block Fortran
C  ================================================================
C
C      Subroutine PMVMUL
C
C      Purpose:
C        This subroutine multiplies a matrix in vector form
C        and a vector.
C
C  ================================================================
C
C      Arguments
C        a      -  matrix in vector form
C        b      -  vector
C        c      -  result vector
C        neq    -  order of vector and square matrix
C        jdiag  -  array of diagonal addresses for a
C
C      subroutine PMVMUL(a,jdiag,b,neq,c)

       recursive subroutine PMVMUL(a,jdiag,b,neq,c)

       real*8 a(1), b(1), c(1)
       integer jdiag(1), neq

       do 100 i=1,neq
         c(i) = a(jdiag(i))*b(i)
100    continue

       do 200 i=2,neq
         do 300 j=jdiag(i-1)+1,jdiag(i)-1
           k = jdiag(i) - j
           c(i) = c(i) + a(j)*b(i-k)
300      continue
200    continue

       do 250 i=2,neq
         do 400 j=jdiag(i-1)+1,jdiag(i)-1
           k = jdiag(i) - j
           c(i-k) = c(i-k) + a(j)*b(i)
400      continue
250    continue

       return
       end


C
C  ----------------------------------------------------------------
C
C      Subroutine PMVMAD
C
C      Purpose:
C        Multiply a matrix in vector form and a vector and add the
C        resultant vector multiplied by a constant to a second vector
```

62

```
C        multiplied by a second vector
C
C    ------------------------------------------------------------------
C
C    Arguments
C       a     -  matrix in vector form
C       b     -  vector to be multiplied with matrix
C       c     -  resultant and vector to be added
C       fact1 -  constant multiplier of matrix and first vector
C       fact2 -  constant multiplier of second vector
C       jdiag -  array of diagonal addresses for matrix
C       neq   -  order of vectors and matrix
C
C    subroutine PMVMAD(a,jdiag,b,neq,fact1,c,fact2)

     recursive subroutine PMVMAD(a,jdiag,b,neq,fact1,c,fact2)

     real*8 a(1), b(1),c(1),fact1,fact2
     integer jdiag(1), neq

     do 100 i=1,neq
       c(i) = fact2*c(i) + fact1*a(jdiag(i))*b(i)
100  continue

     do 200 i=2,neq
       do 300 j=jdiag(i-1)+1,jdiag(i)-1
         k = jdiag(i) - j
         c(i) = c(i) + fact1*a(j)*b(i-k)
300      continue
200  continue

     do 250 i=2,neq
       do 400 j=jdiag(i-1)+1,jdiag(i)-1
         k = jdiag(i) - j
         c(i-k) = c(i-k) + fact1*a(j)*b(i)
400      continue
250  continue

     return
     end
```

File: prepfem.f

```
C=Module PREPFEM
C=Purpose Preprocess Structure Finite Element module for ACSIS
C=Author K. Alvin
C=Date May 1990
C=Block Fortran
C    ------------------------------------------------------------------
C
C    Subroutine  PREPFEM
C
C    Purpose:
C        This subroutine prepares the finite element mass,
C        stiffness, and S matrices in reduced profile vector form
```

```
C
C
C   ------------------------------------------------------------------------
C
C      Local variables:
C
C         ak        Element Stiffness matrix
C         sm        Element Mass Matrix
C         lm        Local/Global DOF Mapping vector
C         nseq      Number of element degrees of freedom
C         em,ep     Material and Propety id # for element
C
       subroutine PREPFEM

       include 'shared.inc'

C  LOCAL VARIABLES

       parameter (MAXSEQ=24)
       real*8 sk(MAXSEQ,MAXSEQ),sm(MAXSEQ,MAXSEQ),mc,kc
       integer lm(MAXSEQ),nseq,em,ep

       call RENUM

C  Set up skyline storage profile for global matrices

       call PROFILE(ix,id,jdiag,nnp,nel,4,6,mlen,ndof,mask)

C  Perform automatic domain decomposition

       call DOMDEC

C  Check size of skyline profile against storage limitation

       if (mlen .gt. MAXMLEN) then
        print*, 'PREPFEM: error, global matrix exceeded max. size'
       endif

C  Zero Global Matrices prior to assembly

       call ZEROVECT(stif,mlen)
       call ZEROVECT(mass,mlen)

C  ASSEMBLE EACH ELEMENT MASS AND STIFFNESS

       do 100 n=1,nel

         do 20 k=1,4
           j=ix(k,n)
           if ((etype(n).eq.1).and.(k.gt.2)) j = 0
           do 30 i=1,6
             kk=6*(k-1) + i
             if (j .ne. 0) then
               lm(kk) = id(i,j)
             else
               lm(kk) = 0
             endif
30         continue
20       continue
```

64

```
      if (etype(n) .eq. 1) then
        nseq = 12
        em = emat(n)
        ep = eprop(n)
        call BEAM3D(n,ix(1,n),ix(2,n),ix(3,n),coxyz,mat(1,em),
     .       mat(2,em),mat(3,em),prop(1,ep),prop(5,ep),prop(6,ep),
     .       prop(2,ep),prop(3,ep),prop(4,ep),pin(1,n),sk,sm)
      elseif (ix(1,n) .ne. 0) then
    print*,'PREPFEM:Element type not found,n=',n,'etype=',etype(n)
      endif

C   ADD ELEMENT TO GLOBAL MASS AND STIFFNESS

      call ADDSTF(sk,lm,stif,jdiag,nseq)
      call ADDSTF(sm,lm,mass,jdiag,nseq)

C   SAVE THE ELEMENT STIFFNESS FOR E-BY-E COMPUTATIONS

      call SAVESK(sk,n,nseq)

100   continue

C   ADD LUMPED INERTIAS TO GLOBAL MASS

      do 125 i=1,nnp
        do 130 j=1,6
          if (id(j,i) .eq. 0) goto 130
          k=jdiag(id(j,i))
          mass(k) = mass(k) + inertia(j,i)
130     continue
125   continue

C   ASSEMBLE AND FACTORIZE es (S MATRIX)

      mc = 1. + delta*adamp
      kc = delta*bdamp + delsq
      do 200 i=1,mlen
        es(i) = mc*mass(i) + kc*stif(i)
200   continue

      call SOLVER(es,gs,jdiag,ndof,1)

C   INITIALIZE DISPLACEMENT AND VELOCITY VECTORS

      do 300 i = 1, nnp
        do 350 j = 1,6
          if (id(j,i) .ne. 0) then
            q(id(j,i)) = q0(j,i)
            qdot(id(j,i)) = qdot0(j,i)
          endif
350     continue
300   continue

      return
      end

      subroutine SAVESK(sk,n,nseq)

      include 'shared.inc'
```

65

```
      real*8 sk(nseq,1)
      integer n,nseq

      k=0
      do 10 j=1,nseq
        do 20 i=1,j
          k=k+1
          estifm(k,n)=sk(i,j)
20        continue
10      continue

      return
      end

      subroutine DOMDEC

      include 'shared.inc'

      logical nchk,ndchk(MAXNODE,MAXDOM)
      integer ndom

      do 10 j=1,MAXDOM
        neld(j)=0
        do 20 i=1,nnp
          ndchk(i,j)=.false.
20        continue
10      continue
      ndomain=0

      do 100 n=1,nel

        ndom=0
        nchk=0
        do 200 while (nchk.eq.0)
          ndom=ndom+1
          if (ndom.gt.ndomain) ndomain=ndom
          nchk=1
          if (ndchk(ix(1,n),ndom,) nchk=0
          if (ndchk(ix(2,n),ndom)) nchk=0
          if (nchk.eq.1) then
            eldom(n)=ndom
            ndchk(ix(1,n),ndom)=.true.
            ndchk(ix(2,n),ndom)=.true.
            endif
200       continue

        neld(ndom)=neld(ndom)+1
        elnum(neld(ndom),ndom)=n

100     continue

      return
      end
```

File: profile.f

```
C=Module PROFILE
C=Purpose Compute the number of equations and set profile for K
C=Author Bob Taylor
C=Date who knows
C=Update January 1989 by E. Pramono
C=Block Fortran
      subroutine PROFILE(ix,id,jdiag,nnp,nel,nen,ndof,nad,neq,mask)
C+-------------------------------------------------------------------+C
C     PURPOSE:                                                        C
C         THIS SUBROUTINE COMPUTES THE NUMBER OF EQUATIONS REQUIRED   C
C         TO SOLVE THE PROBLEM BY ELIMINATING RESTRAINED DEGREES OF   C
C         FREEDOM FROM THE SYSTEM OF EQUATIONS. KNOWING THE EQUATION  C
C         NUMBERS COORESPONDING TO THE NODAL DEGREES OF FREEDOM, THE  C
C         DIAGONAL ELEMENT LOCATIONS CAN BE COMPUTED FOR STORING THE  C
C         GLOBAL STIFFNES MATRIX IN COMPACTED VECTOR FORM.            C
C-------------------------------------------------------------------C
C
C     ARGUMENTS
C
      integer  ix(nen,1), id(ndof,1), jdiag(1)
      integer  nnp, nel, nad, neq, mask(1)
C     integer  nnp, nel, nen, ndof, nad, neq, mask(1)
C
C     LOCAL ARGUMENTS
C
      integer i, j, k, l, m, n, j1, k1, l1, m1


C
C     SET UP EQUATION NUMBERS
C
      neq = 0
      do 30 n = 1, nnp
         do 20 m = 1, ndof
            j = id(m,mask(n))
            if (j .eq. 1) goto 10
            neq = neq + 1
            id(m,mask(n)) = neq
            jdiag(neq) = 0
            goto 20
10          id(m,mask(n)) = 0
20       continue
30    continue
C
C
C     COMPUTE COLUMN HEIGHTS
C
      do 80 n = 1, nel
         do 70 m = 1, nen
            m1 = ix(m,n)
            if (m1 .le. 0) goto 70
            do 60 l = 1, ndof
               l1 = id(l,m1)
               if (l1 .eq. 0) goto 60
               do 50 k = m, nen
                  k1 = ix(k,n)
                  if (k1 .le. 0) goto 50
                  do 40 j = 1, ndof
                     j1 = id(j,k1)
                     if (j1 .eq. 0) goto 40
```

```
                    i = MAXO(11,j1)
                    jdiag(i) = MAXO(jdiag(i), IABS(11-j1))
40                  continue
50              continue
60          continue
70      continue
80  continue
C
C
C   COMPUTE DIAGONAL POINTERS
C
    nad = 1
    jdiag(1) = 1
    if (neq .eq. 1) return
    do 90 n = 2, neq
        jdiag(n) = jdiag(n) + jdiag(n-1) + 1
90  continue
    nad = jdiag(neq)
C
    return
    end
C=End Fortran
```

File: read.f

```
C=Module READ
C=Author K. Alvin
C=Date May 1990
C=Block Fortran
C   ---------------------------------------------------------
C
C   Subroutine READFEM
C
C   Purpose:
C       This subroutine reads the data file for the finite
C       element model.
C
C   ---------------------------------------------------------
C
C   Arguments
C       ctype   -   stores code for type of line
C

    subroutine READFEM

C   GLOBALS

    include 'shared.inc'

C   LOCALS

    integer j,n,ctype,GETTYPE
    character*132 aline
    real*8 in

C   INITIALIZE SIZE OF PROBLEM
```

68

```fortran
      nnp = 0
      nel = 0
      ndof = 0
      ndomain = 0

C     IDENTIFY CARD TYPE AND ASSIGN INPUT

10    read(11,1000,end=9999) aline
100   ctype = GETTYPE(aline)
      if (ctype) 10,10,150
150   if (aline(1:4) .eq. 'NODE') goto 200
      if (aline(1:4) .eq. 'TOPO') goto 300
      if (aline(1:4) .eq. 'ATTR') goto 400
      if (aline(1:4) .eq. 'MATE') goto 500
      if (aline(1:4) .eq. 'PROP') goto 600
      if (aline(1:4) .eq. 'FIXI') goto 700
      if (aline(1:4) .eq. 'INIT') goto 800
      if (aline(1:4) .eq. 'INER') goto 900 .
      if (aline(1:4) .eq. 'END ') goto 10
      if (aline(1:4) .eq. 'MESH') goto 10
      print *,'READFEM: Unrecognized card type; ',aline(1:4)
      goto 10

C     READ NODES

200   read(11,1000,end=9999) aline
      ctype = GETTYPE(aline)
      if (ctype) 200,250,100
250   read(aline,*) n,(coxyz(j,n),j=1,3)
      if (n .gt. nnp) nnp = n
      goto 200

C     READ TOPOLOGY

300   read(11,1000,end=9999) aline
      ctype = GETTYPE(aline)
      if (ctype) 300,350,100
350   read(aline,*) n,etype(n),(ix(j,n),j=1,4)
      if (n .gt. nel) nel = n
      goto 300

C     READ ATTRIBUTES

400   read(11,1000,end=9999) aline
      ctype = GETTYPE(aline)
      if (ctype) 400,450,100
450   read(aline,*) n,emat(n),eprop(n),(pin(j,n),j=1,6)
      if (eldom(n).gt.ndomain) ndomain=eldom(n)
      goto 400

C     READ MATERIAL

500   read(11,1000,end=9999) aline
      ctype = GETTYPE(aline)
      if (ctype) 500,550,100
550   read(aline,*) n,(mat(j,n),j=1,3)
      goto 500

C     READ PROPERTIES
```

```
600    read(11,1000,end=9999) aline
       ctype = GETTYPE(aline)
       if (ctype) 600,650,100
650    read(aline,*) n,(prop(j,n),j=1,6)
       goto 600

C      READ FIXITY

700    read(11,1000,end=9999) aline
       ctype = GETTYPE(aline)
       if (ctype) 700,750,100
750    read(aline,*) n,(id(j,n),j=1,6)
       goto 700

C      READ INITIAL CONDITIONS

800    read(11,1000,end=9999) aline
       ctype = GETTYPE(aline)
       if (ctype) 800,850,100
850    read(aline,*) n,j,q0(j,n),qdot0(j,n)
       goto 800

C      READ INERTIA

900    read(11,1000,end=9999) aline
       ctype = GETTYPE(aline)
       if (ctype) 900,950,100
950    read(aline,*) n,j,in
       inertia(j,n)=inertia(j,n)+in
       goto 900

1000   format(a132)
9999   continue

       return
       end
C
C  ----------------------------------------------------------
C
C      Subroutine READCON
C
C      Purpose:
C        This subroutine reads the actuator and sensor
C        locations and the gains for the control system
C
C  ----------------------------------------------------------
C
C      Arguments
C        ctype  -  stores code for type of line
C
C
C      Abbreviations
C        NACT   -  number of actuators
C        NSEN   -  number of sensors
C        BMAT   -  locations of actuators
C        HDMA   -  array of displacement sensor locations
C        HVMA   -  array of velocity sensor locations
C        F1GA   -  control gain matrix
```

```
C         F2GA  -  control gain matrix
C         L1GA  -  state estimator filter gain matrix
C         L2GA  -  state estimator filter gain matrix

      subroutine READCON

      include 'shared.inc'

C     LOCALS

      real*8 val
      integer j,n,ctype,GETTYPE
      character*132 aline

      bval = 0
      hdval = 0
      hvval = 0
      hdbval = 0
      hvbval = 0

C     IDENTIFY CARD TYPE AND ASSIGN INPUT

10    read(12,1000,end=9999) aline
100   ctype = GETTYPE(aline)
      if (ctype) 10,10,150
150   if (aline(1:4) .eq. 'NACT') goto 200
      if (aline(1:4) .eq. 'NSEN') goto 300
      if (aline(1:4) .eq. 'BMAT') goto 400
      if (aline(1:4) .eq. 'HDMA') goto 500
      if (aline(1:4) .eq. 'HVMA') goto 600
      if (aline(1:4) .eq. 'F1GA') goto 700
      if (aline(1:4) .eq. 'F2GA') goto 800
      if (aline(1:4) .eq. 'L2GA') goto 900
      if (aline(1:4) .eq. 'L1GA') goto 1100
      if (aline(1:4) .eq. 'END ') goto 10
      print *,'READCON: Unrecognized card type; ',aline(1:4)
      goto 10

C     READ INPUT CARDS

200   read(12,1000,end=9999) aline
      ctype = GETTYPE(aline)
      if (ctype) 200,250,100
250   read(aline,*) nact
      goto 200

300   read(12,1000,end=9999) aline
      ctype = GETTYPE(aline)
      if (ctype) 300,350,100
350   read(aline,*) nsen
      goto 300

400   read(12,1000,end=9999) aline
      ctype = GETTYPE(aline)
      if (ctype) 400,450,100
450   read(aline,*) i,j,n,val
      bval = bval + 1
      b(bval) = val
      brow(bval) = id(j,i)
```

71

```fortran
      bcol(bval) = n
      goto 400

500   read(12,1000,end=9999) aline
      ctype = GETTYPE(aline)
      if (ctype) 500,550,100
550   read(aline,*) i,j,n,val
      hdval = hdval + 1
      hd(hdval) = val
      hdrow(hdval) = n
      hdcol(hdval) = id(j,i)
      goto 500

600   read(12,1000,end=9999) aline
      ctype = GETTYPE(aline)
      if (ctype) 600,650,100
650   read(aline,*) i,j,n,val
      hvval = hvval + 1
      hv(hvval) = val
      hvrow(hvval) = n
      hvcol(hvval) = id(j,i)
      goto 600

700   read(12,1000,end=9999) aline
      ctype = GETTYPE(aline)
      if (ctype) 700,750,100
750   read(aline,*) i,j,n,val
      f1(n,id(j,i)) = qalpha*val
      goto 700

800   read(12,1000,end=9999) aline
      ctype = GETTYPE(aline)
      if (ctype) 800,850,100
850   read(aline,*) i,j,n,val
      f2(n,id(j,i)) = qbeta*val
      goto 800

900   read(12,1000,end=9999) aline
      ctype = GETTYPE(aline)
      if (ctype) 900,950,100
950   read(aline,*) i,j,n,val
      l2(id(j,i),n) = qbetao*val
      goto 900

1100  read(12,1000,end=9999) aline
      ctype = GETTYPE(aline)
      if (ctype) 1100,1150,100
1150  read(aline,*) i,j,n,val
      l1(id(j,i),n) = qalphao*val
      goto 1100

1000  format(a132)
9999  continue
      return
      end

c
c  ------------------------------------------------------------
c
```

```
C      Function GETTYPE
C
C      Purpose:
C        This function identifies whether a line is a character
C        input, data input or comment.
C
C      -----------------------------------------------------------
C
       function GETTYPE(string)

C      GLOBALS

       character*132 string

C      LOCALS

       integer GETTYPE,ctype(10)
       character*1 head(10)

       data head /'!','@','#','$','%','&','*','C','c',' '/
       data ctype /-1,-1,-1,-1,-1,-1,-1,-1,-1,0/

C      LOGIC

       GETTYPE=1
       do 100 i=1,10
         if (string(1:1) .eq. head(i)) GETTYPE=ctype(i)
100      continue

       return
       end
```

File: solver.f

```
C=Module SOLVER
C=Purpose Solves the system of linear symmetric equations
C=Author who knows
C=Date
C=Update January 1989 by E. Pramono
C=Block Fortran
C      SUBROUTINE SOLVER(BK,BR,JDIAG,NEQ,IFLAG)
       recursive SUBROUTINE SOLVER(BK,BR,JDIAG,NEQ,IFLAG)
C+---------------------------------------------------------------+C
C      PURPOSE:                                                  C
C          THIS SUBROUTINE SOLVES THE SYSTEM OF LINEAR SYMMETRIC  C
C          EQUATIONS IN VECTOR FORM USING THE CROUT REDUCTION     C
C          METHOD.                                               C
C                                                                C
C      ARGUMENTS:                                                C
C          BK    - GLOBAL STIFFNESS EQUATIONS IN VECTOR FORM      C
C          BR    - GLOBAL LOAD VECTOR                            C
C          JDIAG - LOCATION VECTOR FOR DIAGONALS IN [BK]          C
C          NEQ   - NUMBER OF EQUATIONS                           C
C          IFLAG - FLAG INDICATING WHICH FUNCTION IS TO BE PERFORMED  C
C                      1 -> FORWARD REDUCTION                     C
C                      2 -> BACKWARD SUBSTITUTION                 C
```

```
C----------------------------------------------------------------------C
C    ARGUMENTS

         REAL*8  BK(1), BR(1)
         INTEGER JDIAG(1), NEQ, IFLAG

C   LOCAL VARIABLES
         REAL*8  ZERO, EZERO, TOL, DAVAL, DOT, D, RDD, DD
         INTEGER LDFLAG, JR, J, JD, JH, IS, IE, K, JDT
         INTEGER JJ, ID, I, IR, IH


         JJ = 6
C
C    ------------------
C    NEW PARAMETERS
C    ------------------
         ZERO   = 0.0D0
         EZERO  = 0.3D-14
         TOL    = 0.5D-7
         LDFLAG = 0
C
C    ------------------------------------------
C    FACTOR BK TO UT*D*U OR REDUCE R
C    ------------------------------------------
         JR = 0
         DO 70 J = 1, NEQ
            JD = JDIAG(J)
            JH = JD - JR
            IS = J - JH + 2
            IF (JH - 2) 60, 30, 10
C
10          IF (IFLAG .NE. 1) GOTO 50
            IE = J - 1
            K = JR + 2
            ID = JDIAG(IS-1)
C
C    ------------------------------------------------------------
C    IF DIAGONAL IS ZERO COMPUTE A NORM FOR SINGULARITY TEST
C    ------------------------------------------------------------
            JDT = JDIAG(IE) + 1
            IF (BK(JD) .EQ. ZERO .AND. IFLAG .EQ. 1) THEN
               CALL DATEST (BK(JDT), JH-2, DAVAL)
            END IF
C
C    -------------------------------------------------------
C    REDUCE ALL EQUATIONS EXCEPT FIRST ROW AND DIAGONAL
C    -------------------------------------------------------
            DO 20 I = IS, IE
               IR = ID
               ID = JDIAG(I)
               IH = MINO(ID-IR-1,I-IS+1)
               IF (IH .GT. 0) BK(K) = BK(K) - DOT(BK(K-IH), BK(ID-IH), IH)
               K = K + 1
20          CONTINUE
C
C    --------------------------------
C    REDUCE FIRST ROW AND DIAGONAL
```

```
C     ------------------------------------
30        IF (IFLAG .NE. 1) GOTO 50
          IR = JR + 1
          IE = JD - 1
          K = J - JD
          DD = BK(JD)
          DO 40 I = IR, IE
             ID = JDIAG(K+I)
             IF (BK(ID) .EQ. 0.0) GOTO 40
             D = BK(I)
             BK(I) = BK(I)/BK(ID)
             BK(JD) = BK(JD) - D*BK(I)
40        CONTINUE
C
C     ------------------------------------------------
C     CHECK FOR POSSIBLE ERRORS AND PRINT WARNINGS
C     ------------------------------------------------
          RDD = BK(JD)
          IF (DABS(RDD) .LT. TOL*DABS(DD))        WRITE (JJ,2000) J
          IF (DD .LT. ZERO .AND. RDD .GT. ZERO)   WRITE (JJ,2001) J
          IF (DD .GT. ZERO .AND. RDD .LT. ZERO)   WRITE (JJ,2001) J
          IF (DABS(RDD) .LT. EZERO)               WRITE (JJ,2002) J
C
C     ------------------------------------------------
C     COMPLETE RANK TEST FOR A ZERO DIAGONAL TEST
C     ------------------------------------------------
          IF (DD .EQ. ZERO .AND. JH .GT. 0) THEN
             IF (DABS(RDD) .LT. TOL*DAVAL)        WRITE (JJ,2003) J
          END IF
C
C     -------------------------
C     REDUCE RIGHT HAND SIDE
C     -------------------------
50        IF (IFLAG .EQ. 2) BR(J) = BR(J) - DOT(BK(JR+1), BR(IS-1), JH-1)
60        JR = JD
70     CONTINUE
       IF (IFLAG .NE. 2) RETURN.
C
C     -------------------------
C     DIVIDE BY DIAGONAL TERMS
C     -------------------------
       DO 80 I = 1, NEQ
          ID = JDIAG(I)
          IF (BK(ID) .NE. 0.0) BR(I) = BR(I)/BK(ID)
          IF (BR(I) .NE. ZERO) LDFLAG = 1
80     CONTINUE
C
C     -------------------------
C     CHECK FOR ZERO LOAD VECTOR
C     -------------------------
       IF (LDFLAG .EQ. 0)     WRITE(JJ,2004)
C
C     ---------------
C     BACK SUBSTITUTE
C     ---------------
       J = NEQ
       JD = JDIAG(J)
90     D = BR(J)
       J = J - 1
```

75

```fortran
      IF (J .LE. 0) RETURN
      JR = JDIAG(J)
      IF (JD - JR .LE. 1) GOTO 110
      IS = J - JD + JR + 2
      K = JR - IS + 1
      DO 100 I= IS, J
         BR(I) = BR(I) - BK(I+K)*D
100   CONTINUE
110   JD = JR
      GOTO 90
C
C     ----------------
C     WARNING FORMATS
C     ----------------
2000  FORMAT(/'!! WARNING !! 1 - IN SOLVER, LOSS OF AT LEAST 7 DIGITS'
     +        /18X, 'IN REDUCING DIAGONAL OF EQUATION;',4X,I5)
2001  FORMAT(/'!! WARNING !! 2 - IN SOLVER, SIGN OF DIAGONAL CHANGED'
     +        /18X, 'WHEN REDUCING EQUATION;',15X,I5)
2002  FORMAT(/'!! WARNING !! 3 - IN SOLVER, REDUCED DIAGONAL IS ZERO'
     +        /18X, 'FOR EQUATION;',25X,I5)
2003  FORMAT(/'!! WARNING !! 4 - IN SOLVER, RANK FAILURE FOR A ZERO'
     +        /18X, 'UNREDUCED DIAGONAL IN EQUATION;',7X,I5)
2004  FORMAT(/'!! WARNING !! 5 - IN SOLVER, ZERO LOAD VECTOR')
C
      END
C=End Fortran
C=Module DATEST
C=Block Fortran
C     SUBROUTINE DATEST(A,JH,DAVAL)
      recursive SUBROUTINE DATEST(A,JH,DAVAL)
C+----------------------------------------------------------------+C
C                                                                  C
C         TEST FOR RANK                                            C
C                                                                  C
C         INPUTS;                                                  C
C                 A(J)  - COLUMN OF UNREDUCED ELEMENTS IN ARRAY     C
C                 JH    - NUMBER OF ELEMENTS IN COLUMN              C
C                                                                  C
C         OUTPUTS;                                                 C
C                 DAVAL - SUM OF ABSOLUTE VALUES                   C
C                                                                  C
C+----------------------------------------------------------------+C
C
C     ARGUMENTS

      REAL*8  A(1), DAVAL
      INTEGER JH

C     LOCAL ARGUMENTS

      INTEGER J
C
      DAVAL = 0.0D0
      DO 10 J = 1, JH
         DAVAL = DAVAL + DABS(A(J))
10    CONTINUE
C
      RETURN
      END
```

```
c
c
C=End Fortran
C=Module DOT
C=Block Fortran
c       FUNCTION DOT(A,B,N)
        recursive FUNCTION DOT(A,B,N)
C+-------------------------------------------------------------+C
c       PURPOSE:                                                C
c          THIS FUNCTION SUBROUTINE PERFORMS THE DOT PRODUCT OF TWO  C
c          VECTORS.                                             C
c                                                               C
c       ARGUMENTS:                                              C
c          A  - FIRST VECTOR INVOLVED IN DOT PRODUCT            C
c          B  - SECOND VECTOR INVOLVED IN DOT PRODUCT           C
c          N  - NUMBER OF ELEMENTS IN EACH OF THE TWO VECTORS   C
C-------------------------------------------------------------C

        REAL*8 DOT, A(1), B(1)
        INTEGER N
c
        INTEGER I
c
        DOT = 0.0
        DO 10 I = 1, N
            DOT = DOT + A(I)*B(I)
10      CONTINUE
c
        RETURN
        END
C=End Fortran
```

File: nophlag.f

```
C=Module NOPHLAG
C=Author K. Alvin
C=Date July 1990
C=Block Fortran
C    --------------------------------------------------------
C
C     Subroutine NOPHLAG
C
C     Purpose:
C        This subroutine solves for the structural displacement
C        and velocity vectors at the half-step for the phase lag
C        correction loop, and gets new measurement
C
C    --------------------------------------------------------
C
C     Arguments
C        delbeta  -  delta * bdamp
C

        subroutine NOPHLAG(zp)

        real*8 zp(1)
        include 'shared.inc'
```

77

```
C       LOCAL VARIABLES

        integer i
        real*8  v(MAXDOF),delbeta

C       LOGIC
C       ADD APPLIED FORCES TO RHS AND PREPARE MASS MULTIPLIER

        do 10 i=1,ndof
          gs(i) = gs(i) + f(i)
          v(i)  = (1. + delta*adamp)*q(i) + delta*qdot(i)
10        continue

C       SOLVE FOR RIGHT HAND SIDE, gs

        do 77 i = 1,ndof
          gs(i) = delsq*gs(i) + v(i)*mass(jdiag(i))
77        continue

        if (bdamp .ne. 0.) then
          delbeta = delta*bdamp
          call PNVMAD(stif,jdiag,q,ndof,delbeta,gs,1.d0)
          endif

C       SOLVE FOR DISPLACEMENT, q, USING RHS AND MATRIX S

        call SOLVER(es,gs,jdiag,ndof,2)

        do 100 i=1,ndof
          v(i) = (gs(i)-q(i))/delta
100       continue

        call ZEROVECT(zp,nsen)

        do 200 jj = 1,hdval
          i = hdrow(jj)
          j = hdcol(jj)
          zp(i) = zp(i) + hd(jj)*gs(j)
200       continue
        do 250 jj = 1,hvval
          i = hvrow(jj)
          j = hvcol(jj)
          zp(i) = zp(i) + hv(jj)*v(i)
250       continue

        return
        end
```

File:.zerovect.f

78

```
c
c      Subroutine ZEROVECT
c
c      ------------------------------------------------------------
c

       subroutine ZEROVECT(v,n)

       real*8 v(1)
       integer n

       do 100 i=1,n
         v(i) = 0.d0
100      continue

       return
       end
```

File: lu.f

```fortran
      SUBROUTINE LUFACT(A,N,PIVOT,DET,IER,NMAX)
C********************************************************************
C
C      SUBROUTINE FACTOR USES GAUSSIAN ELIMINATION WITH
C      PARTIAL PIVOTING AND IMPLICIT SCALING TO DETERMINE
C      THE L*U DECOMPOSION OF A SQUARE MATRIX "A" OF
C      ORDER N.  THE ALGORITHM ALSO FINDS THE DETERMINENT
C      OF "A".  UPON COMPLETION, THE ELEMENTS OF THE UPPER
C      TRIANGULAR MATRIX "U" ARE CONTAINED IN THEIR RESPECTIVE
C      LOCATIONS IN MATRIX "A".  THE ELEMENTS OF MATRIX "L"
C      ARE CONTAINED IN THE LOWER TRIANGULAR PORTION OF "A",
C      BUT ARE SCRAMBLED WITH RESPECT TO "U" BECAUSE OF ROW
C      INTERCHANGE OPERATIONS NOT PERFORMED ON THE ELEMENTS
C      OF "L".  THE VECTOR PIVOT (SEE BELOW) MUST BE USED TO
C      UNSCRAMBLE "L" IF IT IS TO BE USED FOR OTHER OPERATIONS.
C
C      VARIABLES:   A=FULL SQUARE MATRIX (DOUBLE PRECISION)
C                   N=ORDER OF MATRIX A (INTEGER)
C                   PIVOT=VECTOR CONTAINING A RECORD OF
C                         ROW INTERCHANGES. THE INTEGER
C                         VALUE PIVOT(K) IS THE ROW WHICH
C                         WAS INTERCHANGED WITH ROW K AT
C                         FORWARD ELIMINATION STEP K. (INTEGER)
C                   DET=DETERMINENT OF MATRIX A (DOUBLE PRECISION)
C                   IER=ERROR FLAG.  IF IER=1, THE MATRIX A WAS FOUND
C                       TO BE SINGULAR, AND THE ROUTINE WAS EXITED.  IF
C                       IER=0, THE DECOMPOSITION WAS SUCCESSFUL.
C
C********************************************************************
      INTEGER PIVOT(1),IER,N,I,J,K,IO,NMAX
      REAL*8 A(NMAX,1),S(1000),C(1000),DET,TEMP
      DET=1.0D0
C********************************************************************
C
C      FIND THE ROW NORMALIZING COEFFICIENTS S(I) FOR IMPLICIT SCALING.
C      EXIT ROUTINE IF ANY S(I)=0.0
```

```
C
C******************************************************************
      DO 100 I=1,N
        S(I)=0.0D0
        DO 110 J=1,N
          IF (ABS(A(I,J)).GT.S(I)) S(I)=ABS(A(I,J))
  110     CONTINUE
        IF (S(I).EQ.0) THEN
          IER=1
          DET=0.0D0
          RETURN
          END IF
  100   CONTINUE
C******************************************************************
C
C       START FORWARD ELIMINATION STEP K
C
C******************************************************************
      DO 120 K=1,N-1
C******************************************************************
C
C       DETERMINE PIVOT ELEMENT A(IO,K) BY FINDING THE ROW IO
C       BETWEEN K AND N CONTAINING THE MAXIMUM NORMALIZED
C       VALUE IN  COLUMN K.  SET PIVOT(K)=IO
C
C******************************************************************
        C(K)=0.0D0
        DO 130 I=K,N
          TEMP=ABS(A(I,K)/S(I))
          IF (TEMP.GT.C(K)) THEN
            C(K)=TEMP
            IO=I
            END IF
  130     CONTINUE
        PIVOT(K)=IO
C******************************************************************
C
C       EXIT ROUTINE IF ALL VALUES IN COLUMN K AT OR BELOW
C       THE MAIN DIAGONAL ARE EQUAL TO 0.0
C
C******************************************************************
        IF (C(K).EQ.0.0) THEN
          IER=1
          DET=0.0D0
          RETURN
          END IF
C******************************************************************
C
C       INTERCHANGE ROWS IO AND K FOR COLUMNS K TO N.  SKIP IF IO=K.
C       SET DET=-DET IF ROWS ARE INTERCHANGED.
C
C******************************************************************
        IF (IO.EQ.K) GOTO 150
        DET=-1.0D0*DET
        DO 140 J=K,N
          TEMP=A(K,J)
          A(K,J)=A(IO,J)
          A(IO,J)=TEMP
  140     CONTINUE
```

```
C*******************************************************************
C
C     ELIMINATE COLUMN K BELOW MAIN DIAGONAL BY MULTIPLYING
C     ROW K FROM  COLUMN K TO N BY A(I,K)/A(K,K) AND SUBTRACTING
C     FROM ROW I.  STORE THE MULTIPLIER FOR ROW I IN THE ELIMINATED
C     COLUMN K.  MULTIPLY THE RUNNING PRODUCT DET BY DIAGONAL ELEMENT A(K,K).
C
C*******************************************************************
  150    DO 160 I=K+1,N
            A(I,K)=A(I,K)/A(K,K)
            DO 170 J=K+1,N
              A(I,J)=A(I,J)-A(I,K)*A(K,J)
  170       CONTINUE
  160    CONTINUE
         DET=DET*A(K,K)
  120  CONTINUE
C*******************************************************************
C
C     CHECK LAST ROW/COLUMN FOR SINGULARITY.  IF THERE IS NO ERROR,
C     COMPLETE CALCULATION OF THE DETERMINENT, SET THE ERROR FLAG
C     TO INDICATE NORMAL COMPLETION, AND EXIT.
C
C*******************************************************************
       IF (A(N,N).EQ.0.0) THEN
         IER=1
         DET=0.0D0
         RETURN
         END IF
       DET=DET*A(N,N)
       IER=0
       RETURN
       END


       SUBROUTINE LUSOLVE(A,N,B,PIVOT,NMAX)
C*******************************************************************
C
C                 SUBROUTINE SOLVE
C
C*******************************************************************
       INTEGER PIVOT(1),N,I,J,K,NMAX
       REAL*8 A(NMAX,1),B(1),TEMP
       DO 100 K=1,N-1
         IF (PIVOT(K).EQ.K) GOTO 110
         TEMP=B(K)
         B(K)=B(J)
         B(J)=TEMP
  110    DO 120 I=K+1,N
            B(I)=B(I)-A(I,K)*B(K)
  120    CONTINUE
  100  CONTINUE
       B(N)=B(N)/A(N,N)
       DO 130 I=N-1,1,-1
         DO 140 J=I+1,N
           B(I)=B(I)-A(I,J)*B(J)
  140    CONTINUE
         B(I)=B(I)/A(I,I)
  130  CONTINUE
       RETURN
       END
```

```
C=END FORTRAN
c=DECK FACTA
c=PURPOSE - Factors the A matrix as L U = A, with partial pivoting
c=AUTHOR W K BELVIN, Sept. 24, 1987
c
c  =================================================================
c      Input
c            amat----[n X n] matrix to be factored, destroyed on output
c            np------problem size
c
c      Output
c            amat----contains the LU decomposition
c
c  -----------------------------------------------------------------
       subroutine FACTA(amat,np,nrow,lp)
c
       real*8 amat(*),eta
       integer lp(*)
c
       do 50 i=1,np
   50  lp(i)=i
c
c      Find largest pivot.
c
         do 100 k=1,np-1
         amark=0.
         mmax=0
           do 200 m=k,np
             if (abs(amat(lp(m)+(k-1)*nrow)) .gt. amark) then
               amark=abs(amat(lp(m)+(k-1)*nrow))
               mmax=m
             endif
  200      continue
c
             l=lp(k)
             lp(k)=lp(mmax)
             lp(mmax)=l
c
           do 400 i=k+1,np
             eta=amat(lp(i)+(k-1)*nrow)/amat(lp(k)+(k-1)*nrow)
             amat(lp(i)+(k-1)*nrow)=eta
               do 500 j=k+1,np
                  amat(lp(i)+(j-1)*nrow)=amat(lp(i)+(j-1)*nrow)-
                  eta*amat(lp(k)+(j-1)*nrow)
  500          continue
  400      continue
c
  100 continue
c
       return
       end

C END FORTRAN
c=DECK LUSOLV
c=PURPOSE - Solve L U x = b,
c=AUTHOR W K BELVIN, Sept. 24, 1987
c
c  -----------------------------------------------------------------
```

```
c     First solves L y = b, then U x = y
c
c     Input
c          amat----[n X n] matrix factored by FACTA
c          np--------problem size
c          lp      --pointer vector based on pivoting
c          rhs----RHS of equation
c
c     Output
c          amat----contains the LU decomposition.
c          x-------the solution vector
c
c     ------------------------------------------------------------------
      subroutine LUSOLV(amat,np,nrow,lp,rhs,x)
c
      real*8 amat(*),x(*),rhs(*) .
      integer lp(*)
c
      do 50 i=1,np
      x(i)=rhs(i)
  50  continue
c
c     Solve Lower System----------------------------------------------
c**** Outer loop

      do 100 k=1,np
        rhs(k)=x(lp(k))
        if (rhs(k) .eq. 0.) go to 100
c
c**** Inner loop
c
        do 200 i=k+1,np
          x(lp(i))=x(lp(i))-amat(lp(i)+(k-1)*nrow)*rhs(k)
 200     continue
 100  continue
c.
c     Solve Upper System----------------------------------------------
c
      do 300 k=np,1,-1
        x(k)=rhs(k)/amat(lp(k)+(k-1)*nrow)
          do 400 i=1,k-1
            rhs(i)=rhs(i)-x(k)*amat(lp(i)+(k-1)*nrow)
 400      continue
 300  continue
      return
      end
```

File: prepcon.f

```
C=Module PREPCON
C=Purpose Preprocess control analysis module for ACSIS
C=Author K. Alvin
C=Date June 1990
C=Block Fortran
C     ------------------------------------------------------------------
C
C     Subroutine PREPCON
```

```fortran
c
c       Purpose:
c           This subroutine prepares ec, the control prediction integration
c           matrix and eo, the observer construct matrix S (M+delta*D+delsq*K)
c
c       ==========================================================================
c
c

        subroutine PREPCON

        include 'shared.inc'

c       LOCAL VARIABLES

        real*8 mc,kc
        integer ier

c       LOGIC

        call READCON

c       Form Control Prediction Integration Coefficient Matrix
c
c           contype = -1  :  Full State Feedback
c           contype =  0  :  Luenberger Observer
c           contype = +1  :  Kalman Filter

        do 10 i = 1,nact + nsen
          do 20 j = 1,nact + nsen
            ec(i,j) = 0.d0
20        continue
10      continue

        if (contype) 100,200,400

100     ncsi = nact

        do 110 i = 1,nact
          do 120 jj = 1,bval
            j = bcol(jj)
            k = brow(jj)
            ec(i,j) = ec(i,j) + delta*f2(i,k)*b(jj)/mass(jdiag(k))
120       continue
110     continue

        goto 600

200     ncsi = nact + nsen

        do 210 i = 1,nact
          do 220 jj = 1,bval
            j = bcol(jj)
            k = brow(jj)
            ec(i,j) = ec(i,j) + delta*f2(i,k)*b(jj)/mass(jdiag(k))
220       continue
          do 240 j = nact+1,ncsi
            do 250 k = 1,ndof
              ec(i,j) = ec(i,j) + delta*f2(i,k)*l2(k,j-nact)
```

84

```
250         continue
240       continue
210     continue
      do 260 ii = 1,hvval
        i = nact + hvrow(ii)
        do 270 jj = 1,bval
          j = bcol(jj)
          k = brow(jj)
          if (hvcol(ii) .ne. k) goto 270
          ec(i,j) = ec(i,j) + delta*hv(ii)*b(jj)/mass(jdiag(k))
270       continue
        do 290 j = nact+1,ncsi
          k = hvcol(ii)
          ec(i,j) = ec(i,j) + delta*hv(ii)*l2(k,j-nact)
290       continue
260     continue

      goto 600

400   ncsi = nact + nsen

      do 470 i = 1,nact
        do 480 jj = 1,bval
          j = bcol(jj)
          k = brow(jj)
          ec(i,j) = ec(i,j) + delta*f2(i,k)*b(jj)/mass(jdiag(k))
480       continue
        do 500 j = nact+1,ncsi
          do 510 k = 1,ndof
            ec(i,j) = ec(i,j) + delta*f2(i,k)*l2(k,j-nact)/
     .                   mass(jdiag(k))
510       continue
500     continue
470     continue
      do 520 ii = 1,hvval
        i = nact + hvrow(ii)
        do 530 jj = 1,bval
          j = bcol(jj)
          k = brow(jj)
          if (hvcol(ii) .ne. k) goto 530
          ec(i,j) = ec(i,j) + delta*hv(ii)*b(jj)/mass(jdiag(k))
530       continue
        do 550 j = nact+1,ncsi
          k = hvcol(ii)
          ec(i,j) = ec(i,j) + delta*hv(ii)*l2(k,j-nact)/
     .                   mass(jdiag(k))
550       continue
520     continue

600   continue

      do 1100 i = 1,ncsi
        ec(i,i) = ec(i,i) + 1.d0
1100    continue

C     FACTORIZE ec

      call FACTA(ec,ncsi,MAXCSI,pivot)
```

```fortran
      if (ier .eq. 1) then
        print *,'PREPCON: Singular Matrix for Control Integration'
        endif

C     Form Observer Integration Coefficient Matrix, eo

      mc = 1. + delta*adamp
      kc = delta*bdamp + delsq
      do 1200 i=1,mlen
        eo(i) = mc*mass(i) + kc*stif(i)
1200    continue

C     FACTORIZE eo

      call SOLVER(eo,go,jdiag,ndof,1)

C     Initialize Observer States

      call ZEROVECT(qe,ndof)
      call ZEROVECT(qedot,ndof)
      call ZEROVECT(pe,ndof)

      return
      end
```

File: control.f

```fortran
C=Module CONTROL
C=Author K. Alvin
C=Date May 1990
C=Block Fortran
C     -------------------------------------------------------------------
C
C
C     Subroutine CONTROL
C
C     Purpose:
C         This subroutine carries out the numeric integration of one time
C         step of the control system.
C
C     -------------------------------------------------------------------
C
C
C     Arguments
C        qep     - estimated displacement vector at half time step
C        qedotp  - estimated velocity vector at half time step
C        pp      - generalized momentum (f-D*qedotp-K*qep)
C        z       - measured sensor output

      subroutine CONTROL(z)

      include 'shared.inc'
      real*8 z(1)

C     LOCAL VARIABLES

      real*8 qep(MAXDOF),qedotp(MAXDOF),pp(MAXDOF),v(MAXDOF)
```

```
C     LOGIC
C
C     Form RHS of Control Prediction Equation Set
C
C        contype = -1  :  Full State Feedback
C        contype =  0  :  Luenberger Observer with L1 = 0
C        contype = +1  :  Kalman Filter w/generalized momentum variable

      call ZEROVECT(gc,ncsi)

      if (contype) 100,200,300

100   continue

      do 110 i = 1,ndof
        qe(i) = q(i)
        qedot(i) = qdot(i)
110     continue

200 , continue

      do 210 i = 1,ndof
        qep(i) = qe(i) + delta*qedot(i)
        qedotp(i) = qedot(i)
        pp(i)  = f(i) - mass(jdiag(i))*adamp*qedotp(i)
        v(i) = qep(i) + bdamp*qedotp(i)
210     continue

      call PNVMAD(stif,jdiag,v,ndof,-1.d0,pp,1.d0)

      do 220 i=1,nact
        do 230 j = 1,ndof
          gc(i) = gc(i) - f1(i,j)*qep(j) - f2(i,j)*(qedot(j) +
     .           delta*pp(j)/mass(jdiag(j)))
230       continue
220     continue

      if (ncsi .eq. nact) goto 600

      do 240 i=nact+1,ncsi
        k = i - nact
        gc(i) = z(k)
240     continue
      do 245 ii = 1,hdval
        i = hdrow(ii) + nact
        j = hdcol(ii)
        gc(i) = gc(i) - hd(ii)*qep(j)
245     continue
      do 250 ii = 1,hvval
        i = hvrow(ii) + nact
        j = hvcol(ii)
        gc(i) = gc(i) - hv(ii)*(qedot(j)+delta*pp(j)/mass(jdiag(j)))
250     continue

      goto 600

300   continue

      do 310 i = 1,ndof
```

```fortran
          qep(i) = qe(i)
          pp(i) = f(i) - mass(jdiag(i))*adamp*qep(i)/delta
          v(i) = (1 + bdamp/delta)*qep(i)
310       continue

          call PNVMAD(stif,jdiag,v,ndof,-1.d0,pp,1.d0)

          do 320 i=1,nact
            do 330 j = 1,ndof
              gc(i) = gc(i) - f1(i,j)*qep(j) - f2(i,j)*(pe(j) +
     .             delta*pp(j))/mass(jdiag(j))
330         continue
320       continue
          do 340 i=nact+1,ncsi
            k = i - nact
            gc(i) = z(k)
340       continue
          do 345 ii = 1,hdval
            i = hdrow(ii) + nact
            j = hdcol(ii)
            gc(i) = gc(i) - hd(ii)*qep(j)
345       continue
          do 350 ii = 1,hvval
            i = hvrow(ii) + nact
            j = hvcol(ii)
            gc(i) = gc(i) - hv(ii)*(pe(j) + delta*pp(j))/mass(jdiag(j))
350       continue

C     FIND r, CONTROL AND STATE CORRECTION FORCES

600       call LUSOLV(ec,ncsi,MAXCSI,pivot,gc,r)

          do 610 j=1,nact
            u(j) = r(j)
610       continue
          do 620 j=nact+1,ncsi
            gamma(j-nact) = r(j)
620       continue

C     FIND CONTROL CONTRIBUTION TO RHS VECTOR FOR
C     OBSERVER AND STRUCTRE

          do 710 i=1,ndof
            gs(i) = 0.d0
            go(i) = 0.d0
            gk(i) = 0.d0
710       continue
          do 720 jj=1,bval
            i = brow(jj)
            j = bcol(jj)
            gs(i) = gs(i) + b(jj)*u(j)
            go(i) = go(i) + b(jj)*u(j)
            gk(i) = gk(i) + b(jj)*u(j)
720       continue
          if (contype .eq. 0) then
            do 725 i = 1,ndof
              do 730 j=1,nsen
                go(i) = go(i) + mass(jdiag(i))*12(i,j)*gamma(j)
730           continue
```

```
725         continue
      elseif (contype .eq. 1) then
         do 735 i = 1,ndof
            do 740 j=1,nsen
               go(i) = go(i) + (l2(i,j)+mass(jdiag(i))*l1(i,j)/delta)
                           *gamma(j)
               gk(i) = gk(i) + l2(i,j)*gamma(j)
740         continue
735      continue
         endif

      return
      end
```

File: secorder.f

```
C=Module SECORDER
C=Author K. Alvin
C=Date May 1990
C=Block Fortran
C     ----------------------------------------------------------------
C
C     Subroutine SECORDER
C
C     Purpose:
C
C        Solves the second-order dynamical equation:
C
C           Mx" + Dx' + Kx = f + g
C
C        at time (n+1) given f(n+1/2), g(n+1/2) and x,x' at n by
C        the midpoint implicit integration rule.
C        Step size is 2*delta.
C
C        D is of the form (alpha*M + beta*K), f is an applied force,
C        and g is assumed to be other applied force from a feedback
C        control loop.  The matrix E is the factored form of the
C        integration coefficient matrix: E=(M + delta*D + delta^2*K).
C
C     ----------------------------------------------------------------
C
C     Arguments:
C
C        m        -  matrix M
C        k        -  matrix K
C        alpha    -  scalar alpha
C        beta     -  scalar beta
C        f        -  Force vector f(n+1/2)
C        g        -  Feedback force vector g(n+1/2)
C        e        -  martix E
C        x        -  Variable vector x(n)
C        xd       -  Variable vector x'(n)
C        delta    -  Half of integration time step
C        delsq    -  delta^2
C        jdiag    -  Diagonal location pointer for M,K,E matrices
C        ndof     -  Number of equations and length of q
```

```fortran
c      v          - mass multiplier for RHS preparation
c      delbeta    - delta * beta

c   subroutine SECORDER(m,k,alpha,beta,f,g,e,x,xd,
c  .       delta,delsq,jdiag,ndof,MAXDOF)

    recursive subroutine SECORDER(m,k,alpha,beta,f,g,e,x,xd,
   .       delta,delsq,jdiag,ndof,MAXDOF)

c   ARGUMENTS

    real*8 m(1),k(1),alpha,beta,f(1),g(1),e(1)
    real*8 x(1),xd(1),delta,delsq
    integer jdiag(1),ndof,MAXDOF

c   LOCAL VARIABLES

    integer i
    real*8  v(3000),delbeta

c   LOGIC
c   ADD APPLIED FORCES TO RHS AND PREPARE MASS MULTIPLIER

    do 10 i=1,ndof
      g(i) = g(i) + f(i)
      v(i) = (1. + delta*alpha)*x(i) + delta*xd(i)
10    continue

c   SOLVE FOR RIGHT HAND SIDE, g

    do 77 i=1,ndof
      g(i) = delsq*g(i) + v(i)*m(jdiag(i))
77    continue

    if (beta .ne. 0.) then
      delbeta = delta*beta

c   Activate EBE computations for internal force by using STIFFRC
c   subroutine.  Otherwise use PMVMAD (profile matrix/vector mult-add

c     call PMVMAD(k,jdiag,x,ndof,delbeta,g,1.d0)
      call STIFFRC(x,delbeta,g)
      endif

c   SOLVE FOR DISPLACEMENT, q, USING RHS AND MATRIX E

    call SOLVER(e,g,jdiag,ndof,2)

    do 100 i=1,ndof
      xd(i) = 2.*(g(i) - x(i))/delta - xd(i)
      x(i)  = 2.*g(i) - x(i)
100   continue

    return
    end
```

File: measure.f

```
C=Module MEASURE
C=Author K. Alvin
C=Date May 1990
C=Block Fortran
C   ----------------------------------------------------------------
C
C     Subroutine MEASURE
C
C     Purpose:
C       This subroutine stores new measured sensor data by using the
C       previous displacement and velocity vectors at the sensor
C       locations
C
C   ----------------------------------------------------------------
C
C     Arguments
C       zp  -  measured sensor data array
C
      subroutine MEASURE(zp)

      include 'shared.inc'
      real*8 zp(1)

      call ZEROVECT(zp,nsen)

      do 100 jj = 1,hdval
        i = hdrow(jj)
        j = hdcol(jj)
        zp(i) = zp(i) + hd(jj)*q(j)
100     continue
      do 200 jj = 1,hvval
        i = hvrow(jj)
        j = hvcol(jj)
        zp(i) = zp(i) + hv(jj)*qdot(j)
200     continue

      return
      end
```

File: eigens.f

```
C=Module EIGENS
C=Purpose Find Eigenmodes given Mass, Stiffness Matrices
C=Author K. Alvin
C=Date   March 1990
C=Block Fortran
C   ----------------------------------------------------------------
C
C     subroutine EIGENS
C
C   ----------------------------------------------------------------
C
C   COMMON AND GLOBALS
```

```fortran
      include 'shared.inc'

C     LOCAL VARIABLES

      parameter(NVM=100,MNNVM=MAXDOF*NVM,MXCNV=NVM*(NVM+1)/2)
      integer isl(MAXDOF),nvec,i,j,k,kk,out
      real*8  vl(MNNVM),vr(MNNVM),akk(MXCNV),amm(MXCNV)
      real*8  xx(NVM,NVM),eigv(NVM),eigold(NVM)
      real*8  toleig,toljac,omega,fhz

      toleig=.0001
      out = 13

      toljac = toleig
      nvec = min0(2*neig,100)
      nvec = min0(nvec,ndof)

C     SET UP ISL VECTOR

      isl(1) = 1
      do 50 j=2,ndof
        isl(j) = j - jdiag(j) + jdiag(j-1) + 1
50      continue

C     CALL EIGENSOLVER

      call SSPACE(stif,mass,vl,vr,akk,amm,xx,eigv,eigold,isl,
     .          jdiag,neig,nvec,ndof,toleig,toljac,out)

C     WRITE OUTPUT

      write(out,*) 'EIGEN ANALYSIS RESULTS:'
      write(out,*) '                            RADIAL       CYCLIC'
      write(out,*) ' MODE      EIGENVALUE     FREQUENCY    FREQUENCY'
      write(out,*) ' ----      ----------     ---------    ---------'
      write(out,*)
      do 100 i=1,neig
        omega = dsqrt(eigv(i))
        fhz   = omega/(2*3.141592654)
        write(out,'(i5,3(3x,g12.5))') i,eigv(i),omega,fhz
100     continue

      write(out,*) 'EIGENVECTORS:'
      do 200 j=1,neig,5
        write(out,*)
        do 300 i=1,ndof
          k = ndof*(j-1) + i
          write(out,'(i5,5(1x,g12.5))') i,(vr(kk),kk=k,k+4*ndof,ndof)
300       continue
200     continue

      write(out,*) 'MASS MATRIX DIAGONAL:'
      do 400 i=1,nnp
       do 450 j=1,6
        if (id(j,i).ne.0) then
          write(out,*) i,j,id(j,i),mass(jdiag(id(j,i)))
          endif
450     continue
```

```
400    continue

       return
       end
C=End Fortran
```

File: singeig.f

```
       SUBROUTINE SSPACE (AK,AM,VL,VR,AKK,AMM,XX,EIGV,EIGOLD,ISL,
      1   IDIAG,NEIG,NVEC,NDOF,TOLEIG,TOLJAC,NW)
c-----------------------------------------------------------------
c
c     input :
c
c             AK     : stiffness matrix      (profile values) (NDOF)
c             AM     : consistent mass matrix  (profile values) (NDOF)
c             ISL    : stores in position "i" the row # of tip of
c                      column "i" (NDOF)
c             IDIAG  : position of diagonal terms in profile    (NDOF)
c             NEIG   : # of required eigenvalues
c             NVEC   : # of subspace vectors
c             NDOF   : # of degrees of freedom
c             TOLEIG : tolerance for eigenvalues convergence
c             TOLJAC : tolerance for Jacobi convergence
c             NW     : logical unit number for output
c
c     output:
c
c             VL(NDOF,NVEC)             : working array
c                 - VL(.,1..NRMOD)      : AM times rigid modes
c                 - VL(.,NRMOD..NVEC)   : subspace at the previous step
c
c             VR(NDOF,NVEC)             : eigen-vectors
c                 - VR(.,1..NRMOD)      : rigid modes
c                 - VR(.,NRMOD..NVEC)   : subspace at this step (eigenvectors)
c
c             AKK(NVEC*(NVEC + 1)/2)    : stiffness matrix in the subspace
c             AMM(NVEC*(NVEC + 1)/2)    : consistent mass matrix in the subspace
c             XX(NVEC*NVEC)             : subspace eigenvectors
c
c             EIGV(NVEC)                : current eigenvalues
c                 - EIGV(1..NRMOD)      : 0 eigen-values
c                 - EIGV(NRMOD..NVEC)   : following eigenvalues > 0
c
c             EIGOLD(NVEC)              : same as EIGV
c
c-----------------------------------------------------------------

       IMPLICIT REAL*8 (A-H,O-Z)
       DIMENSION AK(1),AM(1),VL(NDOF,NVEC),VR(NDOF,NVEC),AKK(1),
      1   AMM(1),XX(NVEC*NVEC),EIGV(1),EIGOLD(1),ISL(1),IDIAG(1)
C
       WRITE (NW,1003) NEIG,NVEC,NDOF,TOLEIG
C
       CALL INVECT (AK,AM,VL,VR,IDIAG,NDOF,NVEC)
       CALL FACT (AK,IDIAG,ISL,NDOF,NW)
       CALL NULL (AK,AM,VL,VR,IDIAG,ISL,NDOF,NRMOD)
```

```
C
C              NRMOD   : # of rigid modes
C
       WRITE (NW,1004) NRMOD
       NSUB=NVEC-NRMOD
C
       CALL ORTHO (VR,VL,NDOF,NRMOD,NVEC)
C
       NIT=0
       NSMAX=15
       NITMAX=16
       NVEC1=NVEC-1
       DO 5 I=1,NVEC
    5  EIGOLD(I)=0.0
C
  500  NIT=NIT+1
       WRITE (NW,1000) NIT
C
       CALL SOLVES (AK,VL(1,NRMOD+1),VR(1,NRMOD+1),IDIAG,ISL,NDOF,NSUB)
       CALL ORTHO (VL,VR,NDOF,NRMOD,NVEC)
C
       IJ=0
       DO 10 J=NRMOD+1,NVEC
C
C          CALCULATE THE UPPER PART OF AKK (SYMMETRIC)
C
           DO 10 I=NRMOD+1,J
              TR=0.0
              DO 11 K=1,NDOF
   11            TR=TR+VL(K,I)*VR(K,J)
              IJ=IJ+1
              AKK(IJ)=TR
   10  CONTINUE
C
       CALL MULT (AM,VR(1,NRMOD+1),VL(1,NRMOD+1),ISL,IDIAG,NSUB,NDOF)
C
       IJ=0
       DO 20 J=NRMOD+1,NVEC
C
C          CALCULATE THE UPPER PART OF AMM (SYMMETRIC)
C
           DO 20 I=NRMOD+1,J
              TR=0.0
              DO 21 K=1,NDOF
   21            TR=TR+VL(K,I)*VR(K,J)
              IJ=IJ+1
              AMM(IJ)=TR
   20  CONTINUE
C
       CALL JACOBI (AKK,AMM,XX,EIGV(NRMOD+1),NSMAX,TOLJAC,NSUB,NW)
C
C      ORDER EIGENVALUES & EIGENVECTORS
C
   30  IS=0
       DO 40 I=NRMOD+1,NVEC1
          IF (EIGV(I+1).GE.EIGV(I)) GO TO 40
          IS=1
          TR=EIGV(I+1)
          EIGV(I+1)=EIGV(I)
```

94

```
           EIGV(I)=TR
           DO 41 J=1,NSUB
              TR=XX(J+(I-NRMOD)*NSUB)
              XX(J+(I-NRMOD)*NSUB)=XX(J+(I-NRMOD-1)*NSUB)
   41         XX(J+(I-NRMOD-1)*NSUB)=TR
   40   CONTINUE
        IF (IS.EQ.1) GO TO 30
C
C    SUBSPACE CONVERGENCE TEST
C
        ICONV=0
        DO 50 I=NRMOD+1,NVEC
           TR=DABS((EIGOLD(I)-EIGV(I))/EIGV(I))
           EIGOLD(I)=EIGV(I)
           EIGV(I)=TR
           IF (TR.GT.TOLEIG.AND.I.LE.NEIG) ICONV=1
   50   CONTINUE
        WRITE (NW,1001) (EIGV(I),I=1,NVEC)
        IF (ICONV.EQ.0) GO TO 100
C
        IF (NIT.LE.NITMAX) GO TO 70
        WRITE (NW,1002)
        GO TO 100
C
C    UPDATE EIGEN VECTORS
C
   70   DO 80 I=1,NDOF
           DO 80 J=1,NSUB
              TR=0.0
              DO 81 K=1,NSUB
   81            TR=TR+VR(I,K+NRMOD)*XX(K+(J-1)*NSUB)
              VL(I,J+NRMOD)=TR
   80   CONTINUE
        DO 90 I=1,NDOF
           DO 90 J=NRMOD+1,NVEC
   90         VR(I,J)=VL(I,J)
        GO TO 500
C
C    CALCULATE FINAL EIGENVECTORS
C
  100   DO 110 I=1,NDOF
           DO 110 J=1,NSUB
              TR=0.0
              DO 111 K=1,NSUB
  111            TR=TR+VL(I,K+NRMOD)*XX(K+(J-1)*NSUB)
              VR(I,J+NRMOD)=TR
  110   CONTINUE
        DO 112 I=1,NVEC
  112      EIGV(I)=EIGOLD(I)
C
        RETURN
C
 1000 FORMAT (5X,12HITERATION NO,I5)
 1001 FORMAT (6(2X,1PE10.3))
 1002 FORMAT (5X,24HWE ACCEPT CURRENT VALUES)
 1003 FORMAT (//20X,'SUBSPACE ITERATION ROUTINE'//' NB OF EIGENVALUES=',
     1 I5/' NB OF VECTOR=',I5/' NB OF DOF=',I5/' TOLERANCE=',1PE10.3/)
 1004 FORMAT (' NB OF RIGID MODES=',I5//)
C
```

95

```
      END
CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC
      SUBROUTINE INVECT (AK,AM,VL,VR,IDIAG,NDOF,NVEC)
      IMPLICIT REAL*8 (A-H,O-Z)
      DIMENSION AK(1),AM(1),VL(1),VR(NDOF,NVEC),IDIAG(1)
C
      ND=NDOF/NVEC
C
      DO 10 I=1,NDOF
         II=IDIAG(I)
         VR(I,1)=AM(II)
         VL(I)=AM(II)/AK(II)
         DO 10 J=2,NVEC
            VR(I,J)=0.0
   10 CONTINUE
C
      LL=NDOF-ND
C
      DO 20 J=2,NVEC
         TR=0.0
C
         DO 30 I=1,LL
            IF (VL(I).LT.TR) GO TO 30
            TR=VL(I)
            IJ=I
   30    CONTINUE
C
         DO 40 I=LL,NDOF
            IF (VL(I).LE.TR) GO TO 40
            TR=VL(I)
            IJ=I
   40    CONTINUE
C
         VL(IJ)=0.0
         LL=LL-ND
         VR(IJ,J)=1.0
C
   20 CONTINUE
C
      RETURN
      END
CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC
      SUBROUTINE MULT (AM,VR,VL,ISL,IDIAG,NVEC,NDOF)
      IMPLICIT REAL*8 (A-H,O-Z)
      DIMENSION AM(1),VR(NDOF,NVEC),VL(NDOF,NVEC),ISL(1),IDIAG(1)

      DO 500 IV=1,NVEC
         DO 100 I=1,NDOF
            TR=0.0
            IJ=IDIAG(I)
            IK=ABS(ISL(I))
            KK=I
            DO 110 K=IK,I
               TR=TR+AM(IJ)*VL(KK,IV)
               IJ=IJ-1
               KK=KK-1
  110       CONTINUE
C
            IF (I.EQ.NDOF) GO TO 99
```

```
                IK=I+1
                DO 120 K=IK,NDOF
                    IF (I.LT.ABS(ISL(K))) GO TO 120
                    IJ=IDIAG(K)-K+I
                    TR=TR+AM(IJ)*VL(K,IV)
  120           CONTINUE
   99           VR(I,IV)=TR
  100       CONTINUE
  500   CONTINUE

        RETURN
        END
CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC
        SUBROUTINE JACOBI (AK,AM,XX,EIGV,NSMAX,TOL,N,NW)
        IMPLICIT REAL*8 (A-H,O-Z)
        DIMENSION AK(1),AM(1),XX(N,N),EIGV(1)
C
C   INITIALIZE
C
        ZERO=0.0
        TWO=2.0
        DO 10 I=1,N
            II=I*(I-1)/2+I
            IF (AK(II).LE.ZERO.OR.AM(II).LE.ZERO) GO TO 900
            EIGV(I)=AK(II)/AM(II)
            DO 20 J=1,N
                XX(I,J)=ZERO
   20       CONTINUE
            XX(I,I)=1.0
   10   CONTINUE
C
C   SET COUNTER
C
        NSWEEP=0
        NR=N-1
  500   NSWEEP=NSWEEP+1
C
C   CHECK IF ZEROOING IS REQUIRED
C
        EPS=0.01**NSWEEP
        EPS=EPS*EPS
        DO 150 J=1,NR
            IIK=J+1
            DO 150 K=IIK,N
                JJ=J*(J-1)/2+J
                KK=K*(K-1)/2+K
                JK=K*(K-1)/2+J
                EPSAK=(AK(JK)*AK(JK))/(AK(JJ)*AK(KK))
                EPSAM=(AM(JK)*AM(JK))/(AM(JJ)*AM(KK))
                IF (EPSAK.LT.EPS.AND.EPSAM.LT.EPS) GO TO 150
C
C           CALCULATE ROTATION ELEMENTS
C
                AKK=AK(KK)*AM(JK)-AM(KK)*AK(JK)
                AJJ=AK(JJ)*AM(JK)-AM(JJ)*AK(JK)
                AB=(AK(JJ)*AM(KK)-AK(KK)*AM(JJ))/TWO
                CHECK=AB*AB+AKK*AJJ
                IF (CHECK.LT.ZERO) GO TO 900
                SQCH=DSQRT(CHECK)
```

97

```
            D1=AB+SQCH
            D2=AB-SQCH
            DEN=D1
            IF (DABS(D2).GT.DABS(D1)) DEN=D2
            IF (DEN.NE.ZERO) GO TO 45
            CA=ZERO
            CG=-AK(JK)/AK(KK)
            GO TO 50
     45     CA=AKK/DEN
            CG=-AJJ/DEN
C
C
C           PERFORM GENERALIZED ROTATION
C
     50     JP1=J+1
            JM1=J-1
            KP1=K+1
            KM1=K-1
            IF (JM1.LT.1) GO TO 70
            DO 60 I=1,JM1
               IJ=J*JM1/2+I
               IK=K*KM1/2+I
               AKJ=AK(IJ)
               AKK=AK(IK)
               AMJ=AM(IJ)
               AMK=AM(IK)
               AK(IJ)=AKJ+CG*AKK
               AM(IJ)=AMJ+CG*AMK
               AK(IK)=AKK+CA*AKJ
               AM(IK)=AMK+CA*AMJ
     60     CONTINUE
     70     IF (KP1.GT.N) GO TO 90
            DO 80 I=KP1,N
               JI=I*(I-1)/2+J
               KI=I*(I-1)/2+K
               AKJ=AK(JI)
               AMJ=AM(JI)
               AKK=AK(KI)
               AMK=AM(KI)
               AK(JI)=AKJ+CG*AKK
               AM(JI)=AMJ+CG*AMK
               AK(KI)=AKK+CA*AKJ
               AM(KI)=AMK+CA*AMJ
     80     CONTINUE
     90     IF (JP1.GT.KM1) GO TO 110
            DO 100 I=JP1,KM1
               JI=I*(I-1)/2+J
               IK=K*(K-1)/2+I
               AKJ=AK(JI)
               AMJ=AM(JI)
               AKK=AK(IK)
               AMK=AM(IK)
               AK(JI)=AKJ+CG*AKK
               AM(JI)=AMJ+CG*AMK
               AK(IK)=AKK+CA*AKJ
               AM(IK)=AMK+CA*AMJ
    100     CONTINUE
    110     AKK=AK(KK)
            AMK=AM(KK)
            AKJ=AK(JJ)
```

98

```fortran
            AMJ=AM(JJ)
            AK(KK)=AKK+TWO*CA*AK(JK)+CA*CA*AKJ
            AM(KK)=AMK+TWO*CA*AM(JK)+CA*CA*AMJ
            AK(JJ)=AKJ+TWO*CG*AK(JK)+CG*CG*AKK
            AM(JJ)=AMJ+TWO*CG*AM(JK)+CG*CG*AMK
            AK(JK)=ZERO
            AM(JK)=ZERO
C
C           UPDATE EIGENVECTOR FOR THIS ROTATION
C
            DO 120 I=1,N
               XXJ=XX(I,J)
               XXK=XX(I,K)
               XX(I,J)=XXJ+CG*XXK
               XX(I,K)=XXK+CA*XXJ
  120       CONTINUE
  150    CONTINUE
C
C     UPDATE EIGENVALUES & CHECK CONVERGENCE
C
      NT=N*(N+1)/2
      ICONV=0
      DO 160 I=1,N
         II=I*(I-1)/2+I
         IF (AK(II).LE.ZERO.OR.AM(II).LE.ZERO) GO TO 900
         TR=AK(II)/AM(II)
         DEN=(TR-EIGV(I))/TR
         EIGV(I)=TR
         IF (DABS(DEN).GT.TOL) ICONV=1
  160 CONTINUE
      IF (ICONV.EQ.1) GO TO 499
C
C     CHECK OFF DIAGONAL TERMS
C
      EPS=TOL*TOL
      DO 170 J=1,NR
         IIK=J+1
         DO 170 K=IIK,N
            JJ=J*(J-1)/2+J
            KK=K*(K-1)/2+K
            JK=K*(K-1)/2+J
            EPSAK=(AK(JK)*AK(JK))/(AK(JJ)*AK(KK))
            EPSAM=(AM(JK)*AM(JK))/(AM(JJ)*AM(KK))
            IF (EPSAK.LT.EPS.AND.EPSAM.LT.EPS) GO TO 170
            GO TO 499
  170 CONTINUE
C
C     SCALE EIGENVECTORS
C
  179 DO 180 I=1,N
         II=I*(I-1)/2+I
         AKK=DSQRT(AM(II))
         DO 180 J=1,N
            XX(J,I)=XX(J,I)/AKK
  180 CONTINUE
C
      RETURN
C
  499 IF (NSWEEP.LE.NSMAX) GO TO 500
```

```
      WRITE (NW,1000)
      GO TO 179
C
 900  WRITE (NW,1001)
      STOP
C
 1000 FORMAT (5X,34HNO CONVERGENCE AT NSMAX ITERATIONS)
 1001 FORMAT (5X,46HERROR IN JACOBI : MATRIX NOT POSITIVE DEFINITE)
C
      END
CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC
      SUBROUTINE SOLVES (AK,VL,VR,IDIAG,ISL,NDOF,NVEC)
C
C     PURPOSE : SOLVES THE SINGULAR PROBLEM : AK x VL = VR
C               THE SINGULAR COLUMNS INTO AK ARE INDEXED BY
C               THE NEGATIVE VALUES OF ISL, THE CORRESPONDING
C               TERMS OF THE SOLUTION ARE PUT TO 0
C
C
      IMPLICIT REAL*8 (A-H,O-Z)
      DIMENSION AK(1),VL(NDOF,NVEC),VR(NDOF,NVEC),IDIAG(1),ISL(1)
C
      DO 500 IV=1,NVEC

         DO 50 I=1,NDOF
 50         VL(I,IV)=VR(I,IV)
C
C        BACKSUBSTITUTE
C
         DO 100 IC=2,NDOF
            TR=0.0
            IC1=IC-1
            IN1=IDIAG(IC)-IC
            IK=ISL(IC)
            IF (IK.LE.0) THEN
               VL(IC,IV)=0.
               GOTO 100
            ENDIF
            IF (IK.GT.IC1) GO TO 100
            DO 120 K=IK,IC1
               TR=TR+AK(IN1+K)*VL(K,IV)
 120        CONTINUE
            VL(IC,IV)=VL(IC,IV)-TR
 100     CONTINUE
C
C        SOLVE DU=U
C
         DO 150 IC=1,NDOF
            VL(IC,IV)=VL(IC,IV)/AK(IDIAG(IC))
 150     CONTINUE
C
C        BAKSUBSTITUTE
C
         IIC=NDOF
         DO 200 IC=2,NDOF
            TR=VL(IIC,IV)
            IC1=IIC-1
            IK=ISL(IIC)
            IN1=IDIAG(IIC)-IIC
```

```
                IF ((IK.GT.IC1).OR.(IK.LE.0)) GO TO 221
                DO 220 K=IK,IC1
                    VL(K,IV)=VL(K,IV)-AK(IN1+K)*TR
 220            CONTINUE
 221            IIC=IIC-1
 200        CONTINUE
 500    CONTINUE
        RETURN
        END
CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC
        SUBROUTINE FACT (AK,IDIAG,ISL,NDOF,NW)
C
C       PURPOSE : LDLT DECOMPOSITION OF THE POSITIVE SEMI-DEFINITE
C.                MATRIX AK, THE SINGULAR COLUMNS OF AK ARE INDEXED
C                 BY A NEGATIVE VALUE OF IDIAG>
C
C
        IMPLICIT REAL*8 (A-H,O-Z)
        DIMENSION AK(1),IDIAG(1),ISL(1)
C
C       DETERMINE MIN & MAX
C
        TR=DABS(AK(1))
        AMIN=TR
        AMAX=TR
        DO 10 IL=1,NDOF
            TR=DABS(AK(IDIAG(IL)))
            IF (TR.LT.AMIN) AMIN=TR
            IF (TR.GT.AMAX) AMAX=TR
   10   CONTINUE
        ZERO=(AMAX+AMIN)*1.0D-10
C
C       LOOP OVER COLUMN
C
        DO 100 IC=1,NDOF
            MIC=ISL(IC)
            IC1=IC-1
            MIC1=MIC+1
            IN2=IDIAG(IC)-IC
            IF ((MIC.LT.1).OR.(MIC.GT.IC)) GO TO 901
C
C.          CALCULATE GS
C.
            IF (MIC1.GT.IC1) GO TO 150
            DO 120 IL=MIC1,IC1
                IF (IDIAG(IL).LT.0) THEN
                    AK(IN2+IL)=0
                    GOTO 120
                ENDIF
                MIL=ISL(IL)
                IL1=IL-1
                MIM=MAXO(MIL,MIC)
                IN1=IDIAG(IL)-IL
                TR=0.0
                IF (MIM.GT.IL1) GO TO 120
                DO 130 K=MIM,IL1
                    TR=TR+AK(IN1+K)*AK(IN2+K)
 130            CONTINUE
```

```fortran
                IN=IN2+IL
                AK(IN)=AK(IN)-TR
120          CONTINUE
C
C            CALCULATE L&D
C
150          TR=0.0
             IF (MIC.GT.IC1) GO TO 201
             DO 200 IL=MIC,IC1
                IF (IDIAG(IL).LT.0) GOTO 200
                AG=AK(IN2+IL)
                AL=AG/AK(IDIAG(IL))
                AK(IN2+IL)=AL
                TR=TR+AL*AG
200          CONTINUE
201          IN=IDIAG(IC)
             AK(IN)=AK(IN)-TR
             IF (AK(IN).LT.ZERO) IDIAG(IC)=-IDIAG(IC)
100       CONTINUE
          RETURN

901       WRITE (NW,1001)
          STOP

1001 FORMAT (5X,29H***STOP ERROR IN IDIAG VECTOR)
1010 FORMAT (5X,'CONDITIONING OF THE STIFFNESS MATRIX'/2X,
     1 'MIN DIAG TERM=',1PE10.3,' MAX DIAG TERM=',E10.3)

          END
CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC
          SUBROUTINE NULL (AK,AM,VL,VR,IDIAG,ISL,NDOF,NRMOD)
C
C         PURPOSE : CALCULATE THE NULL SPACE OF AK AND PUT AN
C                   ORTHONORMALISED BASE OF THIS SPACE INTO THE
C                   NRMOD FIRST VECTORS OF VR.
C                   VL = AM x VR AFTER EXECUTION
C
C
          IMPLICIT REAL*8 (A-H,O-Z)
          DIMENSION AK(1),AM(1),IDIAG(1),ISL(1),VL(NDOF,*),VR(NDOF,*)
C
C         STORE THE SINGULAR COLUMNS INTO THE BEGINNING OF VR
C
C         THE SINGULAR EQUATION ARE NOW INDEXED BY NEGATIVE VALUES
C         INTO ISL INSTEAD OF IDIAG
C
          NRMOD=0
          DO 1 IC=1,NDOF
             IF (IDIAG(IC).GT.0) GOTO 1
             IDIAG(IC)=-IDIAG(IC)
             NRMOD=NRMOD+1
             MIC=ISL(IC)
             IN=IDIAG(IC)-IC
             DO 2 K=1,MIC-1
2               VR(K,NRMOD)=0.
             DO 3 K=MIC,IC-1
                VR(K,NRMOD)=AK(IN+K)
                AK(IN+K)=0.
3            CONTINUE
```

```fortran
            ISL(IC)=-ISL(IC)
            VR(IC,NRMOD)=-1.
            AK(IDIAG(IC))=1.
            DO 4 K=IC+1,NDOF
    4          VR(K,NRMOD)=0.
    1    CONTINUE
C
C       BAKSUBSTITUTE
C
         DO 200 N=1,NRMOD
            IIC=NDOF
            DO 200 IC=2,NDOF
               TR=VR(IIC,N)
               IC1=IIC-1
               IK=ISL(IIC)
               IN1=IDIAG(IIC)-IIC
               IF ((IK.GT.IC1).OR.(IK.LE.0)) GO TO 221
               DO 220 K=IK,IC1
                  VR(K,N)=VR(K,N)-AK(IN1+K)*TR
  220          CONTINUE
  221          IIC=IIC-1
  200    CONTINUE
C
C       ORTHOGONALISATION
C
         DO 10 N=1,NRMOD
            DO 20 K=1,N-1
               TR=0.
               DO 30 I=1,NDOF
   30             TR=TR+VL(I,K)*VR(I,N)
               DO 40 I=1,NDOF
   40             VR(I,N)=VR(I,N)-TR*VR(I,K)
   20       CONTINUE
            CALL MULT(AM,VL(1,N),VR(1,N),ISL,IDIAG,1,NDOF)
            TR=0.
            DO 50 I=1,NDOF
   50          TR=TR+VR(I,N)*VL(I,N)
            TR=1/SQRT(TR)
            DO 60 I=1,NDOF
               VR(I,N)=VR(I,N)*TR
               VL(I,N)=VL(I,N)*TR
   60       CONTINUE
   10    CONTINUE

         RETURN
         END
CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC
         SUBROUTINE ORTHO(VL,VR,NDOF,NRMOD,NVEC)
C
C       PURPOSE : ORTHOGONALISE THE NSUB LAST COLUMNS OF VL (LAST
C                 EVALUATED SOLUTION) WITH RESPECT TO THE NULL SPACE
C                 OF A, FOR THE AM SCALAR PRODUCT
C
C
         IMPLICIT REAL*8 (A-H,O-Z)
         INTEGER NDOF,NRMOD,NVEC
         DIMENSION VL(NDOF,NVEC),VR(NDOF,NVEC)

         NSUB=NVEC-NRMOD
```

```
      DO 1 J=1,NSUB
        DO 2 I=1,NRMOD
          S=0.
          DO 3 K=1,NDOF
3             S=S+VL(K,I)*VL(K,NRMOD+J)
          DO 4 L=1,NDOF
4             VL(L,NRMOD+J)=VL(L,NRMOD+J)-S*VR(L,I)
2       CONTINUE
1     CONTINUE

      RETURN
      END
```

CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC

File: animout.f

```
C=Module ANIMOUT
C=Author K. Alvin
C=Date June 1990
C=Block Fortran
C   ------------------------------------------------------------
C
C     subroutine ANIMOUT
C
C     Purpose:
C       This subroutine produces an output file to be used to
C       visualize the simulation using MESH.
C
C   ------------------------------------------------------------
C

      subroutine ANIMOUT(q,id,nnp,time,out)
      real*8 q(1),time,v(3)
      integer out,id(6,1),nnp,i,k
      write(out,'(g15.5)') time
      do 100 i=1,nnp
        do 200 k=1,3
          if (id(k,i) .ne. 0) then
            v(k) = q(id(k,i))
          else
            v(k) = 0.
          endif
200       continue
        write(out,1000) (v(k),k=1,3)
100     continue
1000  format(3g15.5)
      return
      end
```

File: stiffrc.f

```
C     subroutine STIFFRC(v,fact,kq)
```

```fortran
      recursive subroutine STIFFRC(v,fact,kq)

      real*8 v(1),fact,kq(1)

      include 'shared.inc'

C   ASSEMBLE EACH ELEMENT MASS AND STIFFNESS

      do 100 ii=1,ndomain

CVD$  CNCALL
      do 110 jj=1,neld(ii)
        n = elnum(jj,ii)
        call ELEFRC(v,fact,kq,n)
110     continue

100   continue

      return
      end

C     subroutine ELEFRC(v,fact,kq,n)

      recursive subroutine ELEFRC(v,fact,kq,n)

      real*8 v(1),fact,kq(1)
      integer n

      include 'shared.inc'

C     LOCAL VARIABLES

      parameter(MAXSEQ=24)
      real*8 sk(MAXSEQ,MAXSEQ)
      integer lm(MAXSEQ),nseq

      do 20 k=1,4
        j=iz(k,n)
        if ((etype(n).eq.1).and.(k.gt.2)) j = 0
        do 30 i=1,6
          kk=6*(k-1) + i
          if (j .ne. 0) then
            lm(kk) = id(i,j)
          else
            lm(kk) = 0
          endif
30        continue
20      continue

      nseq=12

      call LOADSK(sk,n,nseq)

      call ESTIFVM(sk,lm,nseq,v,kq,fact)

      return
      end
```

```
C      subroutine LOADSK(sk,n,nseq)

       recursive subroutine LOADSK(sk,n,nseq)

       include 'shared.inc'

       real*8 sk(nseq,1)
       integer n,nseq

       k=0
       do 10 j=1,nseq
         do 20 i=1,j
           k=k+1
           sk(i,j)=estifm(k,n)
           sk(j,i)=sk(i,j)
20         continue
10       continue

       return
       end
```

File: estifvm.f

```
C      subroutine ESTIFVM(sk,lm,nseq,v,kq,fact)

       recursive subroutine ESTIFVM(sk,lm,nseq,v,kq,fact)

C    ARGUMENTS

       real*8 sk(nseq,1),v(1),kq(1),fact
       integer lm(1),nseq

       do 20 j = 1, nseq
         k = lm(j)
         if (k .eq. 0) goto 20
         do 10 i = 1, nseq
           m = lm(i)
           if (m .eq. 0) goto 10
           kq(m) = kq(m) + sk(i,j)*v(k)*fact
10         continue
20       continue

       return
       end
C=End Fortran
```

File: renum.f

```
C=DECK RENUM
C=PURPOSE- RENUMBERS THE GRID POINTS TO MINIMIZE PROFILE STORAGE
C=AUTHOR W K BELVIN and DUC NGUYEN 7-5-90
C
       subroutine RENUM
C
       include 'shared.inc'
```

```
C
C       Initialize vector
C
        maxtry=2*nnp/3 +1
c.......
        nterms=nnp*maxtry
        do 22 j=1,nterms
22      iadjcy(j)=0
        do 10 i=1,nnp
10      icount(i)=0
c************************
        do 1 i=1,nel
          nodea=ix(1,i)
          nodeb=ix(2,i)
            if ((nodea .eq. 0).or.(nodeb .eq. 0)) go to 1
          icount(nodea)=icount(nodea)+1
          icount(nodeb)=icount(nodeb)+1
          ia=icount(nodea)
          ib=icount(nodeb)
          if(ia.gt.maxtry .or. ib.gt.maxtry) go to 345
          locate=(nodea-1)*maxtry+ia
          iadjcy(locate)=nodeb
          locate=(nodeb-1)*maxtry+ib
          iadjcy(locate)=nodea
1       continue
c************************
        ii=0
        do 37 i=1,nterms
          if ( iadjcy(i) .eq. 0 ) go to 37
          ii=ii+1
          iadjcy(ii)=iadjcy(i)
37      continue
c************************
        last=0
        do 2 i=1,nnp
              last=last+icount(i)
2           continue
        jj=icount(1)
        icount(1)=1
        do 3 i=2,nnp+1
          kk=icount(i)
          icount(i)=icount(i-1)+jj
          jj=kk
3         continue
        go to 556
345     write(6,555)
555     format(2x,'error in dimension for MAXTRY !! ')
556     continue
c************************
        call GENRCM(nnp,icount,iadjcy,perm,mask,xls)
        return
        end
cXXXXXXXXXXXXXXXXXXX
        subroutine genrcm(neqns,xadj,adjncy,perm,mask,xls)
c......reference: computer solution of large sparse positive definite
c......          systems, alan george & joseph w-h liu
c......          (prentive-hall,inc.,englewood cliffs,NJ 07632)
        integer adjncy(1),mask(1),perm(1),xls(1)
```

```
              integer xadj(1),ccsize,i,neqns,nlvl,num,root
              do 100 i=1,neqns
                mask(i)=1
  100         continue
              num=1
              do 200 i=1,neqns
                if( mask(i).eq.0 ) go to 200
                root=i
                call fnroot(root,xadj,adjncy,mask,nlvl,xls,perm(num) )
                call rcm(root,xadj,adjncy,mask,perm(num),ccsize,xls)
                num=num+ccsize
                if(num.gt.neqns) go to 987
  200         continue
c......perm(new node)=old node
c......now, mask(old node)= new node
  987         continue
              do 11 new=1,neqns
                iold=perm(new)
                mask(iold)=new
c               write(6,*) 'iold,mask(iold) = ',iold,mask(iold)
  11          continue
              return
              end
cXXXXX.XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
              subroutine fnroot(root,xadj,adjncy,mask,nlvl,xls,ls)
              integer adjncy(1),ls(1),mask(1),xls(1)
              integer xadj(1),ccsize,j,jstrt,k,kstop,kstrt,
     $            mindeg,nabor,ndeg,nlvl,node,nunlvl,root
              call rootls(root,xadj,adjncy,mask,nlvl,xls,ls)
              ccsize=xls(nlvl+1)-1
              if(nlvl.eq.1 .or. nlvl.eq.ccsize) return
  100         jstrt=xls(nlvl)
              mindeg=ccsize
              root=ls(jstrt)
              if(ccsize.eq.jstrt) go to 400
              do 300 j=jstrt,ccsize
                node=ls(j)
                ndeg=0
                kstrt=xadj(node)
                kstop=xadj(node+1)-1
                do 200 k=kstrt,kstop
                  nabor=adjncy(k)
                  if( mask(nabor) .gt. 0) ndeg=ndeg+1
  200           continue
                if(ndeg.ge.mindeg) go to 300
                root=node
                mindeg=ndeg
  300         continue
  400         call rootls(root,xadj,adjncy,mask,nunlvl,xls,ls)
              if(nunlvl.le.nlvl) return
              nlvl=nunlvl
              if(nlvl.lt.ccsize) go to 100
              return
              end
cXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
              subroutine rcm(root,xadj,adjncy,mask,perm,ccsize,deg)
              integer adjncy(1),deg(1),mask(1),perm(1)
              integer xadj(1),ccsize,fnbr,i,j,jstop,jstrt,k,l,lbegin,
     $            lnbr,lperm,lvlend,nbr,node,root
```

```fortran
      call degree(root,xadj,adjncy,mask,deg,ccsize,perm)
      mask(root)=0
      if(ccsize.le.1) return
      lvlend=0
      lnbr=1
100   lbegin=lvlend+1
      lvlend=lnbr
      do 600 i=lbegin,lvlend
        node=perm(i)
        jstrt=xadj(node)
        jstop=xadj(node+1)-1
        fnbr=lnbr+1
        do 200 j=jstrt,jstop
          nbr=adjncy(j)
          if(mask(nbr).eq.0) go to 200
          lnbr=lnbr+1
          mask(nbr)=0
          perm(lnbr)=nbr
200       continue
        if(fnbr.ge.lnbr) go to 600
        k=fnbr
300     l=k
        k=k+1
        nbr=perm(k)
400     if(l.lt.fnbr) go to 500
        lperm=perm(l)
        if( deg(lperm).le.deg(nbr) ) go to 500
        perm(l+1)=lperm
        l=l-1
        go to 400
500     perm(l+1)=nbr
        if(k.lt.lnbr) go to 300
600     continue
      if(lnbr.gt.lvlend) go to 100
      k=ccsize/2
      l=ccsize
      do 700 i=1,k
        lperm=perm(l)
        perm(l)=perm(i)
        perm(i)=lperm
        l=l-1
700     continue
      return
      end
c XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
      subroutine rootls(root,xadj,adjncy,mask,nlvl,xls,ls)
      integer adjncy(1),ls(1),mask(1),xls(1)
      integer xadj(1),i,j,jstop,jstrt,lbegin,ccsize,lvlend,
     $        lvsize,nbr,nlvl,node,root
      mask(root)=0
      ls(1)=root
      nlvl=0
      lvlend=0
      ccsize=1
200   lbegin=lvlend+1
      lvlend=ccsize
      nlvl=nlvl+1
      xls(nlvl)=lbegin
      do 400 i=lbegin,lvlend
```

```
            node=ls(i)
            jstrt=xadj(node)
            jstop=xadj(node+1)-1
            if(jstop.lt.jstrt) go to 400
            do 300 j=jstrt,jstop
              nbr=adjncy(j)
              if( mask(nbr).eq.0) go to 300
              ccsize=ccsize+1
              ls(ccsize)=nbr
              mask(nbr)=0
300         continue
400       continue
          lvsize=ccsize-lvlend
          if(lvsize.gt.0) go to 200
          xls(nlvl+1)=lvlend+1
          do 500 i=1,ccsize
            node=ls(i)
            mask(node)=1
500       continue
          return
          end
cXXXXXXXXXXXXXXXXXXXX
          subroutine degree(root,xadj,adjncy,mask,deg,ccsize,ls)
          integer adjncy(1),deg(1),ls(1),mask(1)
          integer xadj(1),ccsize,i,ideg,j,jstop,jstrt,
     $            lbegin,lvlend,lvsize,nbr,node,root
          ls(1)=root
          xadj(root)=-xadj(root)
          lvlend=0
          ccsize=1
100       lbegin=lvlend+1
          lvlend=ccsize
          do 400 i=lbegin,lvlend
            node=ls(i)
            jstrt=-xadj(node)
            jstop=iabs( xadj(node+1) ) -1
            ideg=0
            if(jstop.lt.jstrt) go to 300
              do 200 j=jstrt,jstop
              nbr=adjncy(j)
              if( mask(nbr).eq.0 ) go to 200
              ideg=ideg+1
              if(xadj(nbr).lt.0) go to 200
              xadj(nbr)=-xadj(nbr)
              ccsize=ccsize+1
              ls(ccsize)=nbr
200         continue
300       deg(node)=ideg
400       continue
          lvsize=ccsize-lvlend
          if(lvsize.gt.0) go to 100
          do 500 i=1,ccsize
            node=ls(i)
            xadj(node)=-xadj(node)
500       continue
          return
          end
```

File: kfilter.f

```fortran
C       subroutine KFILTER

        recursive subroutine KFILTER

        include 'shared.inc'

        do 10 i = 1,ndof
          go(i) = delsq*(f(i)+go(i))+delta*pe(i)+mass(jdiag(i))*qe(i)
          gk(i) = delta*(f(i)+gk(i))+pe(i)
10        continue

        call SOLVER(eo,go,jdiag,ndof,2)

C       Activate EBE computations for internal force by using STIFFRC
C       subroutine.  Otherwise use PMVMAD (profile matrix/vector mult-add

C       call PMVMAD(stif,jdiag,go,ndof,-delta,gk,1.d0)
        call STIFFRC(go,-delta,gk)

        do 100 i = 1,ndof
          qe(i) = 2.*go(i) - qe(i)
          pe(i) = 2.*gk(i) - pe(i)
100       continue

        return
        end
```